

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name Diesel Fuel
Product description V3017-ULSD-Fuels, diesel
Trade Name ULSD
Product code ULSD, V3017
CAS No. 68334-30-5
EC No. 269-822-7
REACH Registration No. 01-2119484664-27-xxxx

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)	No	Exposure Scenario	Page:
	1	Distribution of Fuels, Diesel	12
	2	Formulation and (re)packing Fuels, Diesel	16
	3	Use as a fuel (Industrial)	20
	4	Use as a fuel (Professional)	24
	5	Use as a fuel (Consumer)	28

Uses advised against Anything other than the above.

1.3 Details of the supplier of the safety data sheet

Company Identification Vitol SA
Place des Bergues 3
1201 Geneva
Switzerland
Telephone +31 10 498 7200
Fax +31 10 452 9545
E-mail (competent person) xreach@vitol.com

1.4 Emergency Telephone Number

Emergency Phone No. +44 (0) 1235 239 670, 24/7
Language(s) spoken: All official European languages.

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation (EC) No. 1272/2008 (CLP) Flam. Liq. 3; H226
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Acute Tox. 4; H332
Carc. 2; H351
STOT RE 2; H373 (Thymus, Liver, Bone marrow)
Aquatic Chronic 2; H411

2.2 Label elements

Product description According to Regulation (EC) No. 1272/2008 (CLP)

V3017-ULSD-Fuels, diesel

Hazard Pictogram(s)



Signal Word(s)

DANGER

Hazard Statement(s)

H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

H315: Causes skin irritation.
H332: Harmful if inhaled.
H351: Suspected of causing cancer.
H373: May cause damage to organs through prolonged or repeated exposure:
Thymus, Liver, Bone marrow
H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331: Do NOT induce vomiting.

2.3 Other hazards

May form explosive mixture with air. The vapour is heavier than air; beware of pits and confined spaces. May cause irritation to eyes and air passages. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

SUBSTANCE	CAS No.	EC No.	%W/W
Diesel fuel	68334-30-5	269-822-7	100

SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Self-protection of the first aider

Eliminate sources of ignition. If it is suspected that fumes are still present, the responder should wear an appropriate mask or self-contained breathing apparatus. Drench contaminated clothing with water before removing to avoid risk of sparks from static electricity. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Avoid all contact. Do not ingest. If swallowed then seek immediate medical assistance.

H2S Warning:

Hydrogen sulphide (H2S) can accumulate in the headspace of storage tanks and reach potentially hazardous concentrations.

Inhalation

If there is any suspicion of inhalation: A self contained breathing apparatus should be worn. Remove to fresh air immediately.

Skin contact

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical advice/attention if you feel unwell.

Eye contact

IF ON SKIN (or hair): Remove contaminated clothing immediately and wash affected skin with plenty of water or soap and water. If irritation (redness, rash, blistering) develops, get medical attention.

Ingestion

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

IF SWALLOWED: Do not induce vomiting because of risk of aspiration into the lungs. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If unconscious, place in recovery position and get medical attention

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

4.2	Most important symptoms and effects, both acute and delayed	immediately. Do not give anything by mouth to an unconscious person. Get medical attention immediately. Do not wait for symptoms to appear. Irritation of the respiratory tract. Causes skin irritation. May cause eye irritation. Aspiration into the lungs may cause chemical pneumonitis, which can be fatal. Ingestion may cause irritation of the gastrointestinal tract. Nausea, vomiting and diarrhoea.
4.3	Indication of any immediate medical attention and special treatment needed Notes to a physician:	Treat symptomatically. IF INHALED: If unconscious, place in recovery position and get medical attention immediately. Administer oxygen if available and artificial respiration if necessary. IF SWALLOWED: Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs.

SECTION 5: FIREFIGHTING MEASURES

5.1	Extinguishing media Suitable extinguishing media Unsuitable extinguishing media	Extinguish with sand or dry chemical. Foam, Carbon dioxide, Water fog or dry powder. Do not use water jet. Direct water jet may spread the fire.
5.2	Special hazards arising from the substance or mixture	Flammable liquid and vapour. Will float and can be reignited on surface water. Decomposes in a fire giving off toxic fumes: A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. May form explosive mixture with air. Prevent liquid entering sewers, basements and any watercourses. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. If sulphur compounds are present in appreciable amounts, combustion products may include also H ₂ S and SO _x (sulfur oxides) or sulfuric acid.
5.3	Advice for firefighters	Fight fire with normal precautions from a reasonable distance. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire. Avoid release to the environment. Dike fire control water for later disposal.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1	Personal precautions, protective equipment and emergency procedures H ₂ S Warning: Small spillages: Large spillages:	Caution - spillages may be slippery. Ensure operatives are trained to minimise exposures. Ensure suitable personal protection during removal of spillages. Eliminate sources of ignition. Shut off leaks if without risk. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid all contact with substance. Ensure adequate ventilation. Do not breathe vapour. Do not ingest. If swallowed then seek immediate medical assistance. Do not use sparking tools. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Product may release Hydrogen Sulphide. Exposure controls - These controls may include: Segregation of areas, Access only to authorised persons, Permit to work systems, Confined space working procedures, Area H ₂ S alarms, Personal H ₂ S alarms, Personal escape sets, H ₂ S awareness training. Please see section 8 for appropriate personal protection equipment. Wear flame-resistant antistatic protective clothing. Evacuate the area and keep personnel upwind. Drench contaminated clothing with water before removing to avoid risk of sparks from static electricity. Avoid all contact. Wear chemical protection suit and breathing apparatus. See Also Section: 8
6.2	Environmental precautions	Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body. If necessary: Dike area to contain the spill and prevent releases to sewers, drains, or other waterways.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

6.3	Methods and material for containment and cleaning up	Provided it is safe to do so, isolate the source of the leak. Use non-sparking equipment when picking up flammable spill. The vapour is heavier than air; beware of pits and confined spaces. Ensure that the equipment is adequately grounded. Allow small spillages to evaporate provided there is adequate ventilation. Wear flame-resistant antistatic protective clothing. Wear chemical protection suit and breathing apparatus.
	Spillages onto land:	In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Dispose of this material and its container as hazardous waste. Small spillages: Allow small spillages to evaporate provided there is adequate ventilation. Wear flame-resistant antistatic protective clothing. Large spillages: Cover spillage with foam to reduce evaporation. Do not use water jet.
	Spillages on water or at sea:	Collect as much as possible in clean container for reuse or disposal. Small spillages: Contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. Large spillages: Open waters should be contained with floating barriers or other mechanical means and recovered, only if this is strictly necessary and if fire/explosion risks can be adequately prevented. Otherwise control the spreading of the spillage, and let the substance evaporate naturally.
6.4	Reference to other sections	See Section: 8,13

SECTION 7: HANDLING AND STORAGE

7.1	Precautions for safe handling	Obtain special instructions before use. Keep away from sources of ignition. - No smoking. Use only outdoors or in a well-ventilated area. Prevent vapour build up by providing adequate ventilation during and after use. May form explosive mixture with air. Take action to prevent static discharges. Use non-sparking tools. All parts of the plant and equipment should be electrically bonded together and connected to earth. Electrical continuity should be checked at regular intervals. Antistatic clothing and footwear should be used. The vapour is heavier than air; beware of pits and confined spaces. Avoid all contact with substance. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe vapour. See Section: 8. Keep good industrial hygiene. Wash hands thoroughly after handling. Contaminated clothing should be thoroughly cleaned.
	H2S Warning:	Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. These controls may include: Segregation of areas, Access only to authorised persons, Permit to work systems, Confined space working procedures, Area H2S alarms, Personal H2S alarms, Personal escape sets, H2S awareness training.
7.2	Conditions for safe storage, including any incompatibilities	Light hydrocarbon vapours can build up in the headspace of containers. These can cause flammability / explosion hazards. Bund storage facilities to prevent soil and water pollution in the event of spillage. Keep only in original packaging. Keep containers properly sealed when not in use. Protect from sunlight. Containers of this material may be hazardous when empty since they retain product residue. Empty container may contain product residue which may result in flammable or explosive vapours inside the container.
	Storage temperature	Stable at ambient temperatures.
	Storage measures	Suitable containers: Mild steel, Stainless steel. Unsuitable containers: Synthetic materials
	Incompatible materials	Keep away from oxidising agents. Strong acids and Alkalis.
7.3	Specific end use(s)	See Section: 1.2 and/or Exposure Scenario

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1	Control parameters	
8.1.1	Occupational exposure limits	Not established

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

8.1.2 **Biological limit value** Not established

8.1.3 **PNECs and DNELs** PNEC: Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.

Diesel fuel Derived No-Effect Level	Oral	Inhalation	Dermal
Industry - Short term - Systemic effects	-	4300 mg/m ³	-
Industry - Long Term - Systemic effects	-	68 mg/m ³	2.9 mg/kg bw/day
Consumer - Long Term - Systemic effects	-	20 mg/m ³	1.3 mg/kg bw/day

8.2 Exposure controls

8.2.1 **Appropriate engineering controls** Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Guarantee that the eye flushing systems and safety showers are located close to the working place.

8.2.2 **Individual protection measures, such as personal protective equipment** Fuels are typically used, transferred and transported in closed systems. If exposure is likely (i.e. during sampling) the following advice may be appropriate. Keep good industrial hygiene. Always wash hands before smoking, eating and drinking. Do not eat, drink or smoke at the work place.

Refer to annexes for exposure scenarios detailing use specific exposure controls.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/ face protection



Use eye protection according to EN 166, designed to protect against liquid splashes.

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.
Recommended: Nitrile rubber

Body protection: Wear anti-static clothing and shoes.
Small scale: Wear suitable coveralls to prevent exposure to the skin.
Large scale: Chemical protection suit

Respiratory protection



When the product is heated/In case of inadequate ventilation wear respiratory protection. The use of a high efficiency filter (EN143) is recommended. Filter type A2.

Closed system(s): Not normally required

Thermal hazards

Not applicable

8.2.3 **Environmental exposure controls** Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state Liquid
Colour Pale yellow

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Odour	Diesel Odour
Melting point/freezing point	- 40 °C - + 6 °C
Boiling point or initial boiling point and boiling range	141 – 462 °C
Flammability	Flammable liquid and vapour.
Lower and upper explosion limit	Not established
Flash point	> 55 °C
Auto-ignition temperature	> 225 °C
Decomposition temperature	Not established
pH	Not established
Kinematic viscosity	> 1.5 mm ² /s at 40 °C
Solubility	Immiscible with water.
Partition coefficient: n-octanol/water (log value)	Not established
Vapour pressure	0.4 kPa at 40°C
Density and/or relative density	0.8 – 0.91 g/cm ³ at 15 °C
Relative vapour density	Not established
Particle characteristics	Not established

9.2 Other information Vapour may create explosive atmosphere.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions. Reacts with - Strong oxidising agents
10.2 Chemical stability	Stable under normal conditions. Hazardous polymerisation will not occur. Product may release Hydrogen Sulphide.
10.3 Possibility of hazardous reactions	Extremely flammable liquid and vapour. May form explosive mixture with air. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Product may release Hydrogen Sulphide.
10.4 Conditions to avoid	Elevated temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight.
10.5 Incompatible materials	Keep away from oxidising agents. Strong acids and Alkalis.
10.6 Hazardous decomposition products	A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. Decomposes in a fire giving off toxic fumes: COx, H ₂ S, Sox.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008	All test data taken from existing ECHA registrations for the substances mentioned.
Acute toxicity - Ingestion	Based upon the available data, the classification criteria are not met. LD50 (oral, rat) mg/kg: >5000 (OECD 401)
Acute toxicity - Inhalation	Acute Tox. 4: Harmful if inhaled. LC50 (inhalation, rat) mg/l/4h: 5.4 (OECD 403)
Acute toxicity - Skin contact	Based upon the available data, the classification criteria are not met. LD50 (skin, rabbit) mg/kg: >4300 (OECD 434)
Skin corrosion/irritation	Skin Irrit. 2; Causes skin irritation. Irritating to skin. (rabbit) (OECD 404)
Serious eye damage/irritation	Based upon the available data, the classification criteria are not met. Not irritating to eyes. (rabbit) (OECD 405)
Respiratory or skin sensitisation	Based upon the available data, the classification criteria are not met. Sensitisation (guinea pig) – Negative (OECD 406)
Germ cell mutagenicity	Based upon the available data, the classification criteria are not met. In vitro: Negative (OECD 476) In vivo: Negative (mouse) (OECD 475)
Carcinogenicity	Carc. 2: May cause cancer. ECHA Registration Endpoint summary: According to EU CLP Classification (EC no. 1272/2008), VGO/Hydrocracked/Distillate fuels are classified for this endpoint.
Reproductive toxicity	Based upon the available data, the classification criteria are not met. Reproductive toxicity: Negative (rat) (OECD 415) Developmental toxicity: Negative (rat) (OECD 414)

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

STOT - Single Exposure	Based upon the available data, the classification criteria are not met. Weight of evidence approach.
STOT - Repeated Exposure	STOT RE 2; May cause damage to organs through prolonged or repeated exposure. Oral: No data available.
Aspiration hazard	Inhalation: NOAEC: 1492 mg/m ³ (rat) Chronic - Systemic effects (OECD 453) Dermal: NOEL: 0.5 ml/kg (rat) Chronic - Systemic effects (OECD 410) Asp. Tox. 1; May be fatal if swallowed and enters airways. Kinematic viscosity: > 1.5 mm ² /s at 40 °C
11.2 Information on other hazards	
11.2.1 Endocrine disrupting properties	This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.
11.2.2 Other information	None known

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Aquatic Chronic 1; Toxic to aquatic life with long lasting effects.
Short Term (acute):	LL50 (Fish) (96 hour) 21 mg/l (OECD 203)
Long term (chronic):	The aquatic toxicity was estimated using the PETROTOX computer model. Estimated NOEL: 0.083 mg/l
12.2 Persistence and degradability	Readily biodegradable (according to OECD criteria).
12.3 Bioaccumulative potential	The product has moderate potential for bioaccumulation. Partition coefficient n-octanol/water (log P O/W) ≥ 3
12.4 Mobility in soil	The product is predicted to have low mobility in soil. Liquid with low volatility.
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB. None of the substances in this product fulfil the criteria for being regarded as a PBT or vPvB substance.
12.6 Endocrine disrupting properties	This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.
12.7 Other adverse effects	None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Disposal should be in accordance with local, state or national legislation. Containers of this material may be hazardous when empty since they retain product residue. Containers must not be punctured or destroyed by burning, even when empty. Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company. Waste code: Fuel Oil (13 07 01) and Diesel fuel (15 01 10). HP3, HP4, HP5, HP6, HP7, HP14
Waste classification according to Directive 2008/98/EC (Waste Framework Directive)	

SECTION 14: TRANSPORT INFORMATION

	ADR/RID	IMDG/ADN
14.1 UN number or ID number	UN 1202	UN 1202
14.2 UN proper shipping name	DIESEL FUEL	DIESEL FUEL
14.3 Transport hazard class(es)	3	3+(N1, N2, N3, CMR, F)
14.4 Packing group	III	III
14.5 Environmental hazards	Environmentally hazardous substance	Classified as a Marine Pollutant.
14.6 Special precautions for user	See Section: 2	
14.7 Maritime transport in bulk according to IMO instruments	No information available.	No information available.
14.8 Additional information	HIN: 30 Tunnel Code: 3 (D/E) Limited Quantity: 5L Special provisions: 640K, 664	EmS: F-E, S-E Limited Quantity: 5L

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU regulations

Seveso

Upper Tier: 25000 tonnes

Lower Tier: 2500 tonnes

15.1.2 National regulations

Germany

Water hazard class: 3

15.2 Chemical Safety Assessment

A REACH chemical safety assessment (CSA) has been carried out. Refer to annexes for exposure scenarios detailing use specific exposure controls.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: New SDS Regulation 2020/878 format, all sections have been updated to include new information. Please review SDS with care.

References:

Existing Safety Data Sheet (SDS).

Harmonised Classification(s) for Diesel fuel (CAS No.68334-30-5).

Existing ECHA registration(s) for Diesel fuel (CAS No.68334-30-5) and Chemical Safety Report.

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Legend

ADR	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
EC	European Community
ECHA	European Chemicals Agency
EU	European Union
DNEL	Derived no effect level
IATA	IATA: International Air Transport Association
ICAO	ICAO: International Civil Aviation Organization
IMDG	IMDG: International Maritime Dangerous Goods
LC50	Lethal Concentration at which 50% of the population is killed
LD50	Lethal Dose at which 50% of the population is killed
LL50	Lethal Loading 50 %
LTEL	Long term exposure limit
NOAEC	No Observed Adverse Effect Concentration
NOEL	No Observed Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	PBT: Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	RID: Regulations concerning the international railway transport of dangerous goods
STEL	Short term exposure limit
UN	United Nations
UVCB	Unknown or Variable Composition, Complex reaction products or Biological materials
vPvB	vPvB: very Persistent and very Bioaccumulative

Hazard classification / Classification code:

Flam. Liq. 3; Flammable liquid, Category 3
Asp. Tox. 1; Aspiration hazard, Category 1
Skin Irrit. 2; Skin corrosion/irritation, Category 2
Acute Tox. 4; Acute Toxicity, Category 4
Carc. 2; Carcinogenicity, Category 2

Hazard Statement(s)

H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H332: Harmful if inhaled.
H351: Suspected of causing cancer.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

Diesel Fuel V3017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

STOT RE 2; Specific target organ toxicity — repeated exposure,
Category 2
Aquatic Chronic 2; Hazardous to the aquatic environment, Chronic ,
Category 2

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vitol SA gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vitol SA accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

See below -

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Diesel Fuel

CAS No.

68334-30-5

EC No.

269-822-7

Summary of Parameters

Physical Parameters			
Vapour pressure (kPa)		<0.5	
Partition Coefficient (log K _{ow})		Individual components vary between 1.99 and 18.02	
Solubility (Water) (mg/l)		Individual components vary between 2.0E+03 mg/l and 4.9E-12 mg/l	
Molecular weight		Not applicable	
Biodegradability		Readily biodegradable.	
Human Health (DNEL)			
Workers	Short term	Inhalation (mg/m ³)	4300
		Dermal (mg/kg bw/day)	No hazard identified
	Long Term	Inhalation (mg/m ³)	68.3
		Dermal (mg/kg bw/day)	2.9
Consumer	Inhalation (mg/m ³)	61.2	
	Dermal (mg/kg bw/day)	1.3	
	Oral (mg/kg bw/day)	1.3	
Environmental Parameters (PNECs)			
Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.			

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Contents

Number	Title	Page:
Exposure scenario 1	Distribution of Fuels, Diesel	12
Exposure scenario 2	Formulation and (re)packing Fuels, Diesel	16
Exposure scenario 3	Use as a fuel (Industrial)	20
Exposure scenario 4	Use as a fuel (Professional)	24
Exposure scenario 5	Use as a fuel (Consumer)	28

Contributing Scenarios

Workers

- PROC1 Use in closed process, no likelihood of exposure
(Storage) Bulk storage with occasional sampling from dedicated sample point
- PROC2 Use in closed, continuous process with occasional controlled exposure
(Storage) Bulk storage with occasional sampling from dedicated sample point
- PROC3 Use in closed batch process (synthesis or formulation)
(Sampling) Sample collection at ventilated sample points
(Elevated) Batch processes at elevated temperatures
(fuel additive) Covers the use as a fuel (or fuel additive), and includes activities associated with its transfer, use, equipment maintenance and handling of waste.
- PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises
- PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
(Vapour) Substance in vapour phase.
- PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
(Manual) Manual transfer/pouring from containers
(Maintenance) Equipment maintenance
(Cleaning) Vessel and container cleaning
- PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
(bulk) Bulk transfer in a closed system
(Drum/batch transfers) Bulk transfers from tote tanks and supply vessels
(refuelling) Refuelling vehicles, light aircraft or marine craft.
- PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
- PROC14 Production of preparations or articles by tableting, compression, extrusion, pelletisation
- PROC15 Use as laboratory reagent
- PROC16 Using material as fuel sources, limited exposure to unburned product to be expected

Environment

- ERC2 Formulation of preparations
- ERC4 Industrial use of processing aids in processes and products, not becoming part of articles
- ERC5 Industrial use resulting in inclusion into or onto a matrix
- ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)
- ERC6b Industrial use of reactive processing aids
- ERC6c Industrial use of monomers for manufacture of thermo-plastics
- ERC7 Industrial use of substances in closed systems
- ERC9a Wide dispersive indoor use of substances in closed systems
- ERC9b Wide dispersive outdoor use of substances in closed systems

Consumer

- PC13 Fuels
(Liquid: Automotive Refuelling)
(Home heating oil)
(Garden equipment use)
(Garden equipment refueling)

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure Scenario 1 – Distribution of Fuels, Diesel (Industrial)

1.0 Contributing Scenarios	
Sector of uses SU	SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
Process category [PROC]	PROC1 PROC2 PROC2 (Storage) PROC3 PROC3 (Sampling) PROC4 PROC8a (Maintenance) PROC8b (Bulk) PROC9 PROC15
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC4 Industrial use of processing aids in processes and products, not becoming part of articles ERC5 Industrial use resulting in inclusion into or onto a matrix ERC6a Industrial use resulting in manufacture of another substance (use of intermediates) ERC6b Industrial use of reactive processing aids ERC6c Industrial use of monomers for manufacture of thermo-plastics ERC7 Industrial use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 1.1b.v1

2.0 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid With potential for aerosol generation
Vapour pressure	<0.5 kPa @ STP
Concentration of substance in product	Covers concentrations up to 100%
Human factors not influenced by risk management	
Potential exposure area	Not defined
Frequency and duration of use	
Exposure duration per day	Covers daily exposures up to 8 hours (unless stated differently).
Exposure duration per year	300
Other operational conditions affecting worker exposure	
Area of use	All contributing scenarios Indoor
Characteristics of the surroundings	Not defined
General measures applicable to all activities	
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.	
General measures (skin irritants)	
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.	
Organisational measures	
PROC8a (Maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Equivalent to LEV - Efficiency of at least: 80%
Technical conditions of use	

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

PROC1, PROC2, PROC2 (Storage), PROC3, PROC8b (Bulk)	Handle substance within a closed system.	
Risk management measures related to human health		
Respiratory protection	No special measures are required.	
Hand and/or Skin protection	PROC4, PROC8b (bulk), PROC 8b (Bulk closed loading), PROC 8b (Bulk open loading), PROC9	Wear suitable gloves tested to EN374. - efficiency of at least 80%
	PROC8a (Maintenance)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. - efficiency of at least 90%
Eye Protection	No special measures are required.	
Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply		
<p>Wear suitable gloves tested to EN374. Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Clear spills immediately. Transfer via enclosed lines Avoid dip sampling. (PROC3 – Sampling) Retain drain downs in sealed storage pending disposal or for subsequent recycle. Apply vessel entry procedures including use of forced supplied air. Wear suitable coveralls to prevent exposure to the skin. (PROC 8a – Maintenance) Fill containers/cans at dedicated fill points supplied with local extract ventilation. (PROC9) Use fume cupboard. (PROC15)</p>		
2.2 Control of environmental exposure		
Amounts used		
Fraction of EU tonnage used in region:	0.1	
Regional use tonnage (tons/year):	3.1E+07	
Fraction of Regional tonnage used locally: tons/year	2.0E-03	
Annual site tonnage (tons/year):	6.1E+04	
Maximum daily site tonnage (kg/day):	2.0E+05	
Environment factors not influenced by risk management		
Flow rate of receiving surface water (m ³ /d):	Not defined (default = 18,000)	
Local freshwater dilution factor:	10	
Local marine water dilution factor:	100	
Operational conditions		
Emission days (days/year):	300 (Continuous release.)	
Release fraction to air from process (initial release prior to RMM):	1.0E-03	
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05	
Release fraction to soil from process (initial release prior to RMM):	1.0E-05	
Note: Common practices vary across sites thus conservative process release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil		
Treat air emission to provide a typical removal efficiency of (%):	90	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	83.3	
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of m ³ (%):	0	
Treat soil emission to provide a typical removal efficiency of (%):	Not defined	
Organisational measures to prevent/limit release from site		
<p>Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.</p>		
Conditions and measures related to municipal sewage treatment plant		
Not applicable as there is no release to wastewater.		
Size of municipal sewage system/treatment plant (m ³ /d)	2000	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.9	
Conditions and measures related to external treatment of waste for disposal		

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

No waste generated.

Substance release quantities after risk management measures

Release to waste water from process (mg/l)	Not defined
Maximum allowable site tonnage (MSafe) (kg/d):	6.7E+05

3. Exposure estimation and reference to its source

3.1 Human exposure prediction

Exposure assessment (method/calculation model) ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m ³)	Risk characterisation ratio (RCR)	dermal exposure(mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	0.01	0.00	0.34	0.12	0.12
PROC2	1.0	0.01	1.37	0.47	0.49
PROC2 (Storage)	1.0	0.01	1.37	0.47	0.49
PROC3	3.0	0.04	0.34	0.12	0.16
PROC3 (Sampling)	3.0	0.04	0.34	0.12	0.16
PROC4	5.0	0.07	1.37	0.47	0.55
PROC8a (Maintenance)	2.0	0.03	1.37	0.47	0.50
PROC8b (bulk)	5.0	0.07	1.37	0.47	0.55
PROC9	5.0	0.07	1.37	0.47	0.55
PROC15	5.0	0.07	0.34	0.12	0.19

3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrорisk model.

Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	5.2E-02 mg/l	5.2E-03 mg/l	5.2E-04 mg/l	4.3E-02 mg/kg ww	5.8E-01 mg/kg ww	3.3E-02 mg/kg ww
Risk characterisation ratio (RCR)	3.4E-02	1.3E-01	1.3E-02	7.6E-04	2.0E-01	1.6E-02

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	1.3E+03	2.4E-02
Inhalation	5.7E+03	1.3E-03

4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

	Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.	
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure Scenario 2 – Formulation and (re)packing Fuels, Diesel

1.0 Contributing Scenarios	
Sector of uses SU	SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
Process category [PROC]	PROC1 PROC2 PROC2 (Storage) PROC3 PROC3 (Sampling) PROC3 (Elevated) PROC4 PROC5 PROC5 (Vapour) PROC8a (Manual) PROC8a (Maintenance) PROC8b (bulk) PROC8b (Drum/batch transfers) PROC9 PROC14 PROC15
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC2 Formulation of preparations
Specific Environmental Release Categories SPERC	ESVOC SpERC 2.2.v1

2.0 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid With potential for aerosol generation
Vapour pressure	<0.5 kPa @ STP
Concentration of substance in product	Covers concentrations up to 100%
Human factors not influenced by risk management	
Potential exposure area	Not defined
Frequency and duration of use	
Exposure duration per day	Covers daily exposures up to 8 hours (unless stated differently).
Exposure duration per year	300
Other operational conditions affecting worker exposure	
Area of use	All contributing scenarios Indoor
Characteristics of the surroundings	Not defined
General measures applicable to all activities	
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.	
General measures (skin irritants)	
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.	
Organisational measures	
PROC8a (Maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Equivalent to LEV - Efficiency of at least: 80%

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Technical conditions of use		
PROC1, PROC2, PROC2 (Storage), PROC3, PROC3 (Elevated), PROC8b (Bulk)	Handle substance within a closed system.	
PROC5 (Vapour)	Provide extract ventilation to points where emissions occur. (Efficiency of at least: 90%)	
PROC 8a (Manual)	Use drum pumps. (Efficiency of at least: 80%)	
Risk management measures related to human health		
Respiratory protection	No special measures are required.	
Hand and/or Skin protection	PROC4, PROC8b (bulk), PROC 8b (Drum/batch transfers), PROC9, PROC14	Wear suitable gloves tested to EN374. - efficiency of at least 80%
	PROC5, PROC8a (Manual)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. - efficiency of at least 90%
Eye Protection	No special measures are required.	
Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply		
Wear suitable gloves tested to EN374. Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling. Clear spills immediately. Transfer via enclosed lines Avoid dip sampling. (PROC3 – Sampling) Retain drain downs in sealed storage pending disposal or for subsequent recycle. Apply vessel entry procedures including use of forced supplied air. Wear suitable coveralls to prevent exposure to the skin. (PROC 8a – Maintenance) Fill containers/cans at dedicated fill points supplied with local extract ventilation. (PROC9) Use fume cupboard. (PROC15)		
2.2 Control of environmental exposure		
Amounts used		
Fraction of EU tonnage used in region:	0.1	
Regional use tonnage (tons/year):	3.0E+07	
Fraction of Regional tonnage used locally: tons/year	1.0E-03	
Annual site tonnage (tons/year):	3.0E+04	
Maximum daily site tonnage (kg/day):	1.0E+05	
Environment factors not influenced by risk management		
Flow rate of receiving surface water (m³/d):	Not defined (default = 18,000)	
Local freshwater dilution factor:	10	
Local marine water dilution factor:	100	
Operational conditions		
Emission days (days/year):	300 (Continuous release.)	
Release fraction to air from process (initial release prior to RMM):	1.0E-02	
Release fraction to wastewater from process (initial release prior to RMM):	2.0E-04	
Release fraction to soil from process (initial release prior to RMM):	1.0E-04	
Note: Common practices vary across sites thus conservative process release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil		
Treat air emission to provide a typical removal efficiency of (%):	0	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	96.7	
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of m³ (%):	35.1	
Treat soil emission to provide a typical removal efficiency of (%):	Not defined	
Organisational measures to prevent/limit release from site		
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.		
Conditions and measures related to municipal sewage treatment plant		
Size of municipal sewage system/treatment plant (m³/d)	2000	
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.9	
Conditions and measures related to external treatment of waste for disposal		

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

No waste generated.

Substance release quantities after risk management measures

Release to waste water from process (mg/l)	Not defined
Maximum allowable site tonnage (MSafe) (kg/d):	1.0E+05

3. Exposure estimation and reference to its source

3.1 Human exposure prediction

Exposure assessment (method/calculation model) ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m ³)	Risk characterisation ratio (RCR)	dermal exposure(mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	0.01	0.00	0.03	0.01	0.01
PROC2	1.0	0.01	1.37	0.47	0.49
PROC2 (Storage)	1.0	0.01	1.37	0.47	0.49
PROC3	3.0	0.04	0.34	0.12	0.16
PROC3 (Elevated)	0.1	0.00	0.34	0.12	0.12
PROC3 (Sampling)	3.0	0.04	0.34	0.12	0.16
PROC4	5.0	0.07	1.37	0.47	0.55
PROC5	5.0	0.07	1.37	0.47	0.55
PROC5 (Vapour)	2.5	0.36	0.07	0.02	0.38
PROC8a (Manual)	2.0	0.03	1.37	0.47	0.50
PROC8a (Maintenance)	2.0	0.03	1.37	0.47	0.50
PROC8b (bulk)	5.0	0.07	1.37	0.47	0.55
PROC8b (Drum/batch transfers)	5.0	0.07	1.37	0.47	0.55
PROC9	5.0	0.07	1.37	0.47	0.55
PROC14	5.0	0.07	0.69	0.24	0.31
PROC15	5.0	0.07	0.34	0.12	0.19

3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	0.3 mg/l	0.03 mg/l	0.003 mg/l	0.05 mg/kg ww	0.7 mg/kg ww	0.07 mg/kg ww
Risk characterisation ratio (RCR)	0.2	0.75	0.075	0.0075	0.91	0.091

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	35.8	0.03

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Inhalation	65.6	0.011
------------	------	-------

4. Evaluation guidance to downstream user		
For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).	
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.	
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure Scenario 3 – Use as a fuel (Industrial)

1.0 Contributing Scenarios	
Sector of uses SU	SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
Process category [PROC]	PROC1 PROC2 PROC2 (Storage) PROC3 (fuel additive) PROC8a (Maintenance) PROC8a (Cleaning) PROC8b (bulk) PROC8b (Drum/batch transfers) PROC16
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC7 Industrial use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 7.12a.v1

2.0 Operational conditions and risk management measures	
2.1 Control of worker exposure	
Product characteristics	
Physical form of product	Liquid With potential for aerosol generation
Vapour pressure	<0.5 kPa @ STP
Concentration of substance in product	Covers concentrations up to 100%
Human factors not influenced by risk management	
Potential exposure area	Not defined
Frequency and duration of use	
Exposure duration per day	Covers daily exposures up to 8 hours (unless stated differently).
Exposure duration per year	300
Other operational conditions affecting worker exposure	
Area of use	All contributing scenarios Indoor
Characteristics of the surroundings	Not defined
General measures applicable to all activities	
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.	
General measures (skin irritants)	
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.	
Organisational measures	
PROC8a (Maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Equivalent to LEV - Efficiency of at least: 80%
PROC8a (Cleaning)	Apply vessel entry procedures including use of forced supplied air. Equivalent to LEV - Efficiency of at least: 80%
Technical conditions of use	
PROC1, PROC2, PROC2 (Storage), PROC3 (fuel additive), PROC8b (bulk), PROC16	Handle substance within a closed system.
Risk management measures related to human health	

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Respiratory protection	No special measures are required.	
Hand and/or Skin protection	PROC8b (bulk), PROC 8b (Drum/batch transfers)	Wear suitable gloves tested to EN374. - efficiency of at least 80%
	PROC8a (Maintenance)	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. - efficiency of at least 90%
Eye Protection	No special measures are required.	

Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply

Wear suitable gloves tested to EN374.
 Ensure material transfers are under containment or extract ventilation.
 Clear transfer lines prior to de-coupling.
 Clear spills immediately.
 Transfer via enclosed lines
 Avoid dip sampling. (PROC3 – Sampling)
 Retain drain downs in sealed storage pending disposal or for subsequent recycle. Apply vessel entry procedures including use of forced supplied air.
 Wear suitable coveralls to prevent exposure to the skin. (PROC 8a – Maintenance)

2.2 Control of environmental exposure

Amounts used

Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tons/year):	3.7E+06
Fraction of Regional tonnage used locally: tons/year	0.4
Annual site tonnage (tons/year):	1.5E+06
Maximum daily site tonnage (kg/day):	5.0E+06

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Not defined (default = 18,000)
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

Operational conditions

Emission days (days/year):	300 (Continuous release.)
Release fraction to air from process (initial release prior to RMM):	0.005
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	0

Note: Common practices vary across sites thus conservative process release estimates used.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Treat air emission to provide a typical removal efficiency of (%):	95
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	98.7
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of m ³ (%):	74.1
Treat soil emission to provide a typical removal efficiency of (%):	Not defined

Organisational measures to prevent/limit release from site

Do not apply industrial sludge to natural soils.
 Sludge should be incinerated, contained or reclaimed.

Conditions and measures related to municipal sewage treatment plant

Not applicable as there is no release to wastewater.	
Size of municipal sewage system/treatment plant (m ³ /d)	2000
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.9

Conditions and measures related to external treatment of waste for disposal

No waste generated.

Substance release quantities after risk management measures

Release to waste water from process (mg/l)	Not defined
Maximum allowable site tonnage (MSafe) (kg/d):	5.0E+06

3. Exposure estimation and reference to its source

3.1 Human exposure prediction

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure assessment (method/calculation model)		ECETOC TRA			
Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m ³)	Risk characterisation ratio (RCR)	dermal exposure(mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	1.0	0.01	1.37	0.47	0.49
PROC2	1.0	0.01	1.37	0.47	0.49
PROC2 (Storage)	1.0	0.01	0.14	0.05	0.06
PROC3 (Fuel additive)	1.0	0.01	0.34	0.12	0.13
PROC8a (Maintenance)	1.0	0.01	1.37	0.47	0.49
PROC8a (Cleaning)	1.0	0.01	1.37	0.47	0.49
PROC8b (bulk)	5.0	0.07	1.37	0.47	0.55
PROC8b (Drum/batch transfers)	5.0	0.07	1.37	0.47	0.55
PROC16	1.0	0.1	0.03	0.01	0.02

3.2 Environmental exposure prediction

Exposure assessment (method/calculation model)	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.
--	--

Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	0.3 mg/l	0.03 mg/l	0.003 mg/l	0.05 mg/kg ww	0.7 mg/kg ww	0.07 mg/kg ww
Risk characterisation ratio (RCR)	0.2	0.75	0.075	0.009	0.91	0.091

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	35.6	0.03
Inhalation	82	0.014

4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure Scenario 4 – Use as a fuel (Professional)

1.0 Contributing Scenarios	
Sector of uses SU	SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process category [PROC]	PROC1 PROC2 PROC1 (Storage) PROC3 (Fuel additive) PROC8a (Maintenance) PROC8a (Cleaning) PROC8b (bulk) PROC8b (Drum/batch transfers) PROC8b (refuelling) PROC16
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC9a Wide dispersive indoor use of substances in closed systems ERC9b Wide dispersive outdoor use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 9.12b.v1

2.0 Operational conditions and risk management measures		
2.1 Control of worker exposure		
Product characteristics		
Physical form of product	Liquid With potential for aerosol generation	
Vapour pressure	<0.5 kPa @ STP	
Concentration of substance in product	Covers concentrations up to 100%	
Human factors not influenced by risk management		
Potential exposure area	Not defined	
Frequency and duration of use		
Exposure duration per day	Covers daily exposures up to 8 hours (unless stated differently).	
Exposure duration per year	365	
Other operational conditions affecting worker exposure		
Area of use	PROC16	Outdoor
	All other PROC's	Indoor
Characteristics of the surroundings	Not defined	
General measures applicable to all activities		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.		
General measures (skin irritants)		
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.		
Organisational measures		
PROC8a (Maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Equivalent to LEV - Efficiency of at least: 80%	
PROC8b (Drum/batch transfers)	Transfer substance using closed system e.g. using drum pump. (Efficiency of at least: 80%)	
Technical conditions of use		
PROC1 (Storage)	Handle substance within a closed system.	
PROC16	In case of Indoor use: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Efficiency of at least: 30%	

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Risk management measures related to human health	
Respiratory protection	No special measures are required.
Hand and/or Skin protection	PROC8b (bulk), PROC 8b (Drum/batch transfers), PROC8b (refuelling)
	PROC8a (Maintenance)
Eye Protection	No special measures are required.
Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear suitable gloves tested to EN374. Ensure material transfers are under containment or extract ventilation. Avoid spillage when withdrawing pump. Clear transfer lines prior to de-coupling. Clear spills immediately. Transfer via enclosed lines Retain drain downs in sealed storage pending disposal or for subsequent recycle. Apply vessel entry procedures including use of forced supplied air. Wear suitable coveralls to prevent exposure to the skin. (PROC 8a – Maintenance)	
2.2 Control of environmental exposure	
Amounts used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tons/year):	6.9E+06
Fraction of Regional tonnage used locally: tons/year	5.0E-04
Annual site tonnage (tons/year):	3.4E+03
Maximum daily site tonnage (kg/day):	9.4E+03
Environment factors not influenced by risk management	
Flow rate of receiving surface water (m ³ /d):	Not defined (default = 18,000)
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Operational conditions	
Emission days (days/year):	365
Release fraction to air from process (initial release prior to RMM):	0.001
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E+05
Note: Common practices vary across sites thus conservative process release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Treat air emission to provide a typical removal efficiency of (%):	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	62.9
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of m ³ (%):	0
Treat soil emission to provide a typical removal efficiency of (%):	Not defined
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and measures related to municipal sewage treatment plant	
Not applicable as there is no release to wastewater.	
Size of municipal sewage system/treatment plant (m ³ /d)	2000
Estimated substance removal from wastewater via domestic sewage treatment (%):	94.9
Conditions and measures related to external treatment of waste for disposal	
Substance release quantities after risk management measures	
Release to waste water from process (mg/l)	Not defined
Maximum allowable site tonnage (MSafe) (kg/d):	6.9E+04

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

3. Exposure estimation and reference to its source

3.1 Human exposure prediction

Exposure assessment (method/calculation model) ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m ³)	Risk characterisation ratio (RCR)	dermal exposure(mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	1.0	0.01	1.37	0.47	0.49
PROC2	1.0	0.01	1.37	0.47	0.49
PROC1 (Storage)	0.01	0.00	0.34	0.12	0.12
PROC3 (Fuel additive)	1.0	0.01	0.34	0.12	0.13
PROC8a (Maintenance)	1.0	0.01	1.37	0.47	0.49
PROC8a (Cleaning)	5.0	0.07	1.37	0.47	0.55
PROC8b (bulk)	5.0	0.07	1.37	0.47	0.55
PROC8b (Drum/batch transfers)	1.0	0.01	1.37	0.47	0.49
PROC8b (refuelling)	5.0	0.07	1.37	0.47	0.55
PROC16	14.0	0.20	0.34	0.12	0.32

3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	2.4E-03 mg/l	2.8E-03 mg/l	2.4E-05 mg/l	4.5E-02 mg/kg ww	0.5 mg/kg ww	0.02 mg/kg ww
Risk characterisation ratio (RCR)	1.6E-03	7.7E-02	6.0E-04	6.6E-03	4.7E-02	1.1E-03

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	31.2	0.02
Inhalation	5.8	0.001

4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

Diesel Fuel V3017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

	levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.	
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Exposure Scenario 5 – Use as a fuel (Consumer)

1.0 Contributing Scenarios	
Sector of uses SU	SU21 Consumer uses: Private households (= general public = consumers)
Process category [PROC]	not applicable
Chemical product category [PC]	PC13 (Automotive – refueling) PC13 (Home heating fuel) PC13 (Liquid, Garden equipment - Use) PC13 (Liquid: Garden equipment - Refuelling)
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC9a Wide dispersive indoor use of substances in closed systems ERC9b Wide dispersive outdoor use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 9.12c.v1

2.0 Operational conditions and risk management measures				
2.1 Control of worker exposure				
Product characteristics				
Physical form of product	liquid			
Concentration of substance in product	Covers percentage substance in the product up to 100 % (unless stated differently).			
Human factors not influenced by risk management				
Potential exposure area	PC13	Chemical product category [PC]	Category	Skin Contact (cm ²)
		PC13 (Automotive); PC13 (Home heating fuel)		Palm of one hand - 210
		PC13 (Liquid: Garden equipment - Refuelling)		Both hands - 420
		PC13 (Liquid, Garden equipment - Use)		Not defined
Frequency and duration of use				
Exposure duration (hours/Event)	PC13	Chemical product category [PC]	Category	Duration
		PC13 (Automotive)		0.05
		PC13 (Liquid, Garden equipment - Use)		2.00
		PC13 (Liquid: Garden equipment - Refuelling); PC13 (Home heating fuel)		0.03
Frequency of use (days per year)	PC13	Chemical product category [PC]	Category	Use frequency (days per year)
		PC13 (Automotive)		52
		PC13 (Home heating fuel)		120
		PC13 (Liquid, Garden equipment - Use); PC13 (Liquid: Garden equipment - Refuelling)		26
Amounts used (g/Event)	PC13	Chemical product category [PC]	Category	Mass (g)
		PC13 (Automotive)		37500
		PC13 (Home heating fuel)		1500
		PC13 (Liquid, Garden equipment - Use); PC13 (Liquid: Garden equipment - Refuelling)		750
Operational conditions				
Area of use				

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Characteristics of the surroundings	Chemical product category [PC]	Category	Room size (m ³)
	PC13	PC13 (Automotive); PC13 (Liquid, Garden equipment - Use)	100 or outdoors
PC13 (Home heating fuel)		20	
PC13 (Liquid: Garden equipment - Refuelling)		34	
Risk management measures			
Respiratory protection	No specific measures identified.		
Hand/Skin protection	No specific measures identified.		
Eye Protection	No specific measures identified.		
2.2 Control of environmental exposure			
Amounts used			
Fraction of EU tonnage used in region:	0.1		
Regional use tonnage (tons/year):	1.9E+07		
Fraction of Regional tonnage used locally: tons/year	5.0E-04		
Annual site tonnage (tons/year):	9.5E+03		
Maximum daily site tonnage (kg/day):	2.6E+04		
Environment factors not influenced by risk management			
Flow rate of receiving surface water (m ³ /d):	Not defined (default = 18,000)		
Local freshwater dilution factor:	10		
Local marine water dilution factor:	100		
Operational conditions			
Emission days (days/year):	365		
Release fraction to air from process (initial release prior to RMM):	1.0E-03		
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05		
Release fraction to soil from process (initial release prior to RMM):	1.0E-05		
Organisational measures to prevent/limit release from site			
No specific measures identified.			
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil			
Treat air emission to provide the required removal efficiency of (%):	0		
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	0		
Treat soil emission to provide a typical removal efficiency of (%):	0		
Note: No specific measures identified. In the event of discharge with no STP ensure that wastes are contained, recycled and discharges are controlled within permitted consents.			
Conditions and measures related to municipal sewage treatment plant			
Size of municipal sewage system/treatment plant (m ³ /d)	2000		
Degradation effectiveness (%)	94.9		
Conditions and measures related to external treatment of waste for disposal			
Combustion emissions limited by required exhaust emission controls. External treatment and disposal of waste should comply with applicable local and/or national regulations.			
Substance release quantities after risk management measures			
Release to waste water from process (mg/l)	Not defined		
Maximum allowable site tonnage (MSafe) (kg/d):	1.8E+05		

3. Exposure estimation and reference to its source

3.1 Human exposure prediction

Exposure assessment (method/calculation model) ECETOC TRA

Note: Oral exposure is not expected to occur.

Inhalation	Dermal	Combined
------------	--------	----------

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017

Process category [PROC]	inhalation exposure* (mg/m ³)	Risk characterisation ratio (RCR)	dermal exposure* (mg/kg bw/day)	Risk characterisation ratio (RCR)	inhalation exposure (mg/m ³)
PC13 (Automotive)	1.10	0.02	0.50	0.39	0.40
PC13 (Home heating fuel)	0.34	0.01	1.16	0.89	0.89
PC13 (Liquid, Garden equipment - Use)	0.51	0.01	0.00	0.00	0.01
PC13 (Liquid: Garden equipment - Refuelling)	0.06	0.00	0.49	0.38	0.38

*Yearly exposure

^Chronic

3.2 Environmental exposure prediction

Exposure assessment (method/calculation model)

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Fuels, Diesel is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore a PNEC is not available for Fuels, Diesel for individual environmental compartments.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	6.7E-03 mg/l	3.2E-03 mg/l	6.7E-05 mg/l	4.8E-02 mg/kg ww	0.5 mg/kg ww	0.02 mg/kg ww
Risk characterisation ratio (RCR)	4.3E-03	8.8E-02	1.7E-03	1.7E-02	6.0E-02	2.3E-03

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	31.3	0.024
Inhalation	5.8	0.001

4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not support the need for a DNEL to be established for other health effects. Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org/en/reach-for-industries-libraries.html).	
Exposure assessment instrument/tool/method	Workers	ECETOC TRA
	environmental exposure	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SAFETY DATA SHEET



Revision: 24 March 2023 Version: 006

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

Diesel Fuel V3017