

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

SECTION 1: IDENTIFICATION

Product identifier

Product name Cat Gasoline
CAS No. 64741-55-5

Other means of identification

Light Catalytic Cracked Naphtha

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Motor fuels.
Uses advised against Anything other than the above.

Details of the supplier of the safety data sheet

Supplier Vitol Inc.
2925 Richmond Ave, 11th Floor
Houston, TX 77098
Telephone (713) 230-1000
Fax 713-230-1185
E-mail (competent person) SDSHOU@vitol.com

Emergency telephone number

Emergency Phone No. Chemtrec: US/Canada: 1-800-424-9300 (24h)
Mexico: 800 681 9531 (24h)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Flammable Liquid, Category 1
Health hazards Aspiration hazard, Category 1
Skin Corrosion/Irritation, Category 2
Specific target organ toxicity — single exposure, Category 3 (Narcotic effects)
Germ cell mutagenicity, Category 1B
Carcinogen, Category 1B
Reproductive toxicity, Category 2
Environmental hazards Hazardous to the aquatic environment, Acute, Category 2
Hazardous to the aquatic environment, Chronic, Category 2

Label elements

Hazard Pictogram(s)



Signal Word(s)

DANGER

Hazard Statement(s)

Extremely flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Obtain special instructions before use.
Do not breathe vapour.
Wear protective gloves/eye protection/face protection.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Do NOT induce vomiting.
Avoid release to environment.
Dispose of contents in accordance with local, state or national legislation.

Other hazards

The vapour is heavier than air; beware of pits and confined spaces. May cause irritation to eyes and air passages. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0% of the mixture consists of ingredients of unknown acute inhaled toxicity.
0% of the mixture consists of ingredients of unknown acute oral toxicity.
0% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Classification: OSHA HCS (29 CFR 1910.1200)

Chemical identity of the substance	%W/W	CAS No.	EC No.
Naphtha (Petroleum), light catalytic cracked	15 - 100	64741-55-5	265-056-2

Hazardous constituents

Chemical identity of the substance	%W/W	CAS No.	EC No.
Hexane (Other Isomers)	0 - 30	96-14-0	202-481-4
Toluene	0 - 10	108-88-3	203-625-9
Xylene (o, m, p isomers)	0 - 10	1330-20-7	215-535-7
1,2,4-trimethylbenzene	0 - 5	95-63-6	202-436-9
Benzene	0 - 5	71-43-2	200-753-7
Butylene	0 - 5	25167-67-3	246-689-3
Cumene	0 - 5	98-82-8	202-704-5
Cyclohexane	0 - 5	110-82-7	203-806-2
Ethylbenzene	0 - 5	100-41-4	202-849-4
Pentane	0 - 5	109-66-0	203-692-4
n-Heptane	0 - 3	142-82-5	205-563-8
N-hexane	0 - 3	110-54-3	203-777-6
Cyclopentane	0 - 2	287-92-3	206-016-6
Naphthalene	0 - 2	91-20-3	202-049-5
Nonane	0 - 2	111-84-2	203-913-4
Hydrogen Sulfide	< 1	7783-06-4	231-977-3

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Self-protection of the first aider

Avoid all contact. Do not breathe vapour. Eliminate sources of ignition. If it is suspected that fumes are still present, the responder should wear an appropriate mask or self-contained breathing apparatus. Drench contaminated clothing with water before removing to avoid risk of sparks from static electricity. Do not use mouth-to-mouth resuscitation. No action should be taken involving personal risk. Wear appropriate personal protective equipment, avoid direct contact. Avoid exposure during pregnancy. Do not ingest. If swallowed then seek immediate medical assistance.

Inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration only if patient is not breathing but do not use mouth to mouth resuscitation. Get medical advice/attention if you feel unwell.

Skin contact

IF ON SKIN (or hair): Remove contaminated clothing immediately and wash affected skin with plenty of water or soap and water. If irritation persists, get medical attention.

Eye contact

IF IN EYES: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention. If irritation persists, get medical attention.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water and give small quantities of water to drink. Do not give anything by mouth to an unconscious person. Get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Do not wait for symptoms to appear.

Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Notes to a physician:

IF SWALLOWED: Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

Extinguish with sand or dry chemical. Foam, Carbon dioxide, Water fog or dry powder

Unsuitable extinguishing media

Do not use water jet. Direct water jet may spread the fire.

Special hazards arising from the substance or mixture

Extremely flammable liquid and vapour. Will float and can be reignited on surface water. A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. May form explosive mixture with air. Prevent liquid entering sewers, basements and any watercourses. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. If sulphur compounds are present in appreciable amounts, combustion products may include also H₂S and SO_x (sulfur oxides) or sulfuric acid.

Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire. Avoid release to the environment. Dike fire control water for later disposal.

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Caution - spillages may be slippery. Ensure operatives are trained to minimise exposures. Ensure suitable personal protection during removal of spillages. Eliminate sources of ignition. Shut off leaks if without risk. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Do not ingest. If swallowed then seek immediate medical assistance. Do not use sparking tools. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Avoid exposure during pregnancy.

Methods and material for containment and cleaning up

Provided it is safe to do so, isolate the source of the leak. Use non-sparking equipment when picking up flammable spill. The vapour is heavier than air; beware of pits and confined spaces. Ensure that the equipment is adequately grounded. Allow small spillages to evaporate provided there is adequate ventilation. Wear flame-resistant antistatic protective clothing. Wear chemical protection suit and breathing apparatus.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Obtain special instructions before use. Keep away from sources of ignition - No smoking. Use only outdoors or in a well-ventilated area. Prevent vapour build up by providing adequate ventilation during and after use. May form explosive mixtures with air. Take action to prevent static discharges. Use non-sparking tools. All parts of the plant and equipment should be electrically bonded together and connected to earth. Electrical continuity should be checked at regular intervals. Antistatic clothing and footwear should be used. The vapour is heavier than air; beware of pits and confined spaces. Avoid all contact with substance. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe vapour. See Section: 8. Keep good industrial hygiene. Wash hands thoroughly after handling. Contaminated clothing should be thoroughly cleaned.

Conditions for safe storage, including any incompatibilities

Light hydrocarbon vapours can build up in the headspace of containers. These can cause flammability / explosion hazards. Bund storage facilities to prevent soil and water pollution in the event of spillage. Keep only in original packaging. Keep containers properly sealed when not in use. Protect from sunlight. Containers of this material may be hazardous when empty since they retain product residue. Empty container may contain product residue which may result in flammable or explosive vapours inside the container.

Storage temperature
Incompatible materials

Stable at ambient temperatures.
Keep away from oxidising agents. Strong Acids and Alkalis.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Hexane (Other Isomers)	96-14-0	100	350	510 [^]	1800	NIOSH
		500	-	1000	-	ACGIH
Toluene	108-88-3	100	375	150	560	NIOSH
		-	-	300	-	OSHA
		20	-	-	-	ACGIH, A4
Xylene	1330-20-7	100	435	150*	655	NIOSH
		100	435	-	-	OSHA
Benzene	71-43-2	0.1	0.32	1 [^]	3.2	NIOSH
		1	-	5	-	OSHA
		0.5	-	2.5	-	ACGIH
Butylene	25167-67-3	250	-	-	-	ACGIH, A4
Cumene	98-82-8	50	245	-	-	NIOSH
		50	245	-	-	OSHA
		50	-	-	-	ACGIH
Cyclohexane	110-82-7	300	1050	-	-	NIOSH
		300	1050	-	-	OSHA
		100	-	-	-	ACGIH
Ethylbenzene	100-41-4	100	435	125*	545*	NIOSH
		100	435	-	-	OSHA
		20	-	-	-	ACGIH
Pentane	109-66-0	120	350	610 [^]	1800 [^]	NIOSH
		1000	2950	-	-	OSHA
		1000	-	-	-	ACGIH
n-Heptane	142-82-5	85	350	440 [^]	1800 [^]	NIOSH
		5000	2000	-	-	OSHA
		400	-	500	-	ACGIH
N-hexane	110-54-3	50	180	-	-	NIOSH
		50	1800	-	-	OSHA
		50	-	-	-	ACGIH, Sk
Cyclopentadiene	542-92-7	75	200	-	-	NIOSH
		75	200	-	-	OSHA
Naphthalene	91-20-3	10	50	15 [^]	75 [^]	NIOSH
		10	50	-	-	OSHA
		10	-	-	-	ACGIH, SK, A3
Nonane	111-84-2	200	1050	-	-	NIOSH
		200	-	-	-	ACGIH
Hydrogen Sulfide	7783-06-4	-	-	10 (1)	15 (1)	NIOSH
		-	-	20	-	OSHA
		1	-	5	-	ACGIH

Note: OSHA PELs 1910.1000 TABLE Z-1/2/3 / NIOSH RELs / ACGIH TLVs

[^]Ceiling limit value (15 min)

(1)

*NIOSH 15 minute average values

Sk - Can be absorbed through skin.

A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histological type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiological studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

A4: Not Classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of the lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.

The other components listed in Section 3 do not have occupational exposure limits.

Biological exposure indicies

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

SUBSTANCE	CAS No.	Determinant	Biological Exposure Indices	Sampling Time	Note
Toluene	108-88-3	Toluene in blood	0.02 mg/l	Prior to last shift of workweek	-
		Toluene in urine	0.03 mg/l	End of shift	-
		o-Cresol in urine with hydrolysis	0.3 mg/g creatinine	End of shift	B
Xylene, o-,m-,p- or mixed isomers	1330-20-7	Methylhippuric acids in urine.	1.5 g/g Creatinine	End of shift	-
Ethylbenzene	100-41-4	Sum of mandelic acid and phenylglyoxylic acid in urine	0.15 g/g Creatinine	End of shift	Ns
Naphthalene	91-20-3	1-Naphthol* + 2-Naphthol*	-	End of shift	Nq, Ns

Source: ACGIH: American Conference of Governmental Industrial Hygienists - Biological Exposure Index (BEI) 2019

Note:

B: Background

Nq: Nonquantitative

Ns: The determinant is nonspecific, since it is also observed after exposure to other chemicals.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Guarantee that the eye flushing systems and safety showers are located close to the working place.

Individual protection measures, such as personal protective equipment

Fuels are typically used, transferred and transported in closed systems. If exposure is likely (i.e. during sampling) the following advice may be appropriate. Keep good industrial hygiene. Always wash hands before smoking, eating and drinking. Do not eat, drink or smoke at the work place. Avoid all contact. Do not breathe vapour. Avoid exposure during pregnancy.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/ face protection



Use eye protection according to EN 166, designed to protect against liquid splashes.

Skin protection



Hand protection: Wear impervious gloves (recommended: EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Protective index 6, corresponding > 480 minutes of permeation time according to EN 374. Efficiency of at least 80%.

Body protection: Wear anti-static clothing and shoes.

Small scale: Wear suitable coveralls to prevent exposure to the skin.
Large scale: Chemical protection suit.

Respiratory protection



When the product is heated / In case of inadequate ventilation wear respiratory protection. The use of a high efficiency filter (recommended: EN143) is recommended. Filter type A1.

Closed system(s): Not normally required.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Light straw to red clear liquid

Odour

Characteristic Gasoline Odor

Odour threshold

Not available.

pH

Not applicable.

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

Melting point/freezing point	> 97 °F (> 36.1 °C)
Initial boiling point and boiling range	Not available.
Flash point	> -58.3 °F (> -50.2 °C) Closed Cup
Evaporation rate	< 10.6
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Upper limit: 7% Lower limit: 1 %
Vapour pressure	4 psi at 38 °C (100 °F) (estimated)
Vapour density	< 4.4 Estimated
Relative density	Not available.
Solubility(ies)	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	> 550 °F (> 287.78 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific Gravity	0.77 (Water=1) (60°F)
Percent volatile	Essentially 100%

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions. Reacts with - Strong oxidising agents
Chemical stability	Stable under normal conditions. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	Extremely flammable liquid and vapour. May form explosive mixture with air. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
Conditions to avoid	Elevated temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight.
Incompatible materials	Keep away from oxidising agents. Strong Acids and Alkalis.
Hazardous decomposition products	A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. Decomposes in a fire giving off toxic fumes: COx, H2S, SOx,

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects	
Acute toxicity - Ingestion	Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) >2,000 mg/kg.
Acute toxicity - Inhalation	Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) > 5 mg/L (Vapour)
Acute toxicity - Skin contact	Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) >2,000 mg/kg.
Skin corrosion/irritation	Skin Corrosion/Irritation, Category 2: Causes skin irritation. Irritating to skin. (rabbit) (OECD 404)
Serious eye damage/irritation	Based upon the available data, the classification criteria are not met.
Respiratory or skin sensitisation	Based upon the available data, the classification criteria are not met.
Germ cell mutagenicity	Germ cell mutagenicity, Category 1B: May cause genetic defects. EU Harmonised Classification
Carcinogenicity	Carcinogen, Category 1A: May cause cancer. EU Harmonised Classification
Reproductive toxicity	Reproductive toxicity, Category 2: Suspected of damaging fertility or the unborn child. EU Harmonised Classification
STOT - single exposure	Specific target organ toxicity — single exposure, Category 3 (Narcotic effects): May cause drowsiness or dizziness.
STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
Aspiration hazard	Aspiration hazard, Category 1: May be fatal if swallowed and enters airways. EU Harmonised Classification.

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

Information on likely routes of exposure

Inhalation	Possible – accidental exposure
Ingestion	Possible – accidental exposure
Skin contact	Possible – accidental exposure
Eye contact	Unlikely – accidental exposure

Early onset symptoms related to exposure

May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Delayed health effects from exposure

May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child.

Exposure levels and health effects

See Section: 8

Interactive effects

None known

Other information

OSHA Designated Carcinogen	Not listed
NIOSH Occupational Carcinogen List	Not listed
NTP Report on Carcinogens	Not listed
IARC Monographs	Not listed

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Hazardous to the aquatic environment, Acute, Category 2: Toxic to aquatic life. LL50: 8.2 mg/L (Fish) (Unnamed publication, 1995)

Persistence and degradability

Hazardous to the aquatic environment, Chronic, Category 2: Toxic to aquatic life with long lasting effects.

Bioaccumulative potential

NOELR: 2.6 g/L (Fish) (OECD 211)

Mobility in soil

Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance

Other adverse effects

Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance

Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance
None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of this material and its container as hazardous waste. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Disposal should be in accordance with local, state or national legislation. Containers of this material may be hazardous when empty since they retain product residue.

SECTION 14: TRANSPORT INFORMATION

	Road/rail (ADR/RID)	Sea transport (IMDG)	Air (ICAO/IATA)
UN number	UN1203	UN1203	UN1203
UN proper shipping name	GASOLINE	GASOLINE	GASOLINE
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	Environmentally hazardous substance	Classified as a Marine Pollutant.	Environmentally hazardous substance
Special precautions for user	See Section: 2		
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable		

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

US Federal Regulations

TSCA Chemical Data Reporting (CDR) Rule	Listed
NIOSH Occupational Carcinogen List	Not listed
EPCRA Section 313	Not listed
CWA 307- Toxic	Not listed
CERCLA - Hazardous Substances	Not listed
CWA Section 311 List of Hazardous Substances	Not listed

US State Regulations

Proposition 65 (California)	Not listed
Massachusetts, New Jersey, Pennsylvania, Rhode Island- State Right to Know Lists	Not listed
New York -State Right to Know Lists	Not listed
Minnesota - State Right to Know Lists	Not listed
Massachusetts – Toxic Use reduction act	Not listed

Non-Regional

IARC Monographs	Not listed
-----------------	------------

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Updated substance / mixture classification. Updated version and date. New format has been issued, all sections have been updated to include new information. Review SDS with care.

Version	3.0
Revision Date	14 April 2021
Date of First Issue	Not available. 2 ND ISSUE RELEASED JUNE, 15 2015

This Safety Data Sheet was prepared in accordance with US Regulation OSHA HCS (29 CFR 1910.1200)

References:

Existing Safety Data Sheet (SDS),
EU Harmonised Classification and Existing ECHA registration for Naphtha (Petroleum), light catalytic cracked (CAS No. 64741-55-5).

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200	Classification procedure
Flammable Liquid, Category 1	Flash point (°C) / Boiling Point (°C)
Aspiration hazard, Category 1	High percentage inclusion of components with Aspiration hazard
Skin Corrosion/Irritation, Category 2	Summation Calculation
Specific target organ toxicity — single exposure, Category 3 (Narcotic effects)	Threshold Calculation
Germ cell mutagenicity, Category 1B	Threshold Calculation
Carcinogen, Category 1B	Threshold Calculation
Reproductive toxicity, Category 2	Threshold Calculation
Hazardous to the aquatic environment, Acute, Category 2	Summation Calculation
Hazardous to the aquatic environment, Chronic, Category 3	Summation Calculation

Legend

ADR/RID	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road / RID: Regulations concerning the international railway transport of dangerous goods
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor (BCF)
CAS	CAS: Chemical Abstracts Service
EC	European Community
EN	European Standard

SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Cat Gasoline

EU	European Union
IATA	International Air Transport Association
ICAO/IATA	ICAO: International Civil Aviation Organization / IATA: International Air Transport Association
IMDG	International Maritime Dangerous Goods
Koc	Soil Adsorption Coefficient
Kow	Partition coefficient: n-octanol/water
LC50	Lethal concentration 50
LD50	Lethal dose 50
LOAEL	Lowest dose adverse effect level
LTEL	Long Term Exposure Limit
NOAEC	No Observed Averse Effect concentration
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	PBT: Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
(Q)SAR	Quantitative structure-activity relationship (QSAR)
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
UN	United Nations
vPvB	very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. VITOL INC gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. VITOL INC accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.