

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product Name Gas oils (petroleum), heavy vacuum  
Product Description V3015a-LIGHT CYCLE OIL-Gas oils (petroleum), heavy vacuum  
Trade Name LIGHT CYCLE OIL  
Product code LCO  
CAS No. 64741-57-7  
EC No. 265-058-3  
REACH Registration No. -

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	No.	Exposure Scenario	Page:
	1	Distribution of Gas oils (petroleum), heavy vacuum	11
	2	Formulation and (re)packing of Gas oils (petroleum), heavy vacuum	15
	3	Use as a fuel (Industrial)	19
	4	Use as a fuel (Professional)	22

Uses Advised Against Anything other than the above.

### 1.3 Details of the supplier of the safety data sheet

Company Identification Vitol SA  
Place des Bergues 3  
P.O. Box 2056  
1211 Geneva 1  
Switzerland  
Telephone +31 10 498 7200  
Fax +31 10 452 9545  
E-Mail (competent person) [xreach@vitol.com](mailto:xreach@vitol.com)

### 1.4 Emergency telephone number

Emergency Phone No. +44 (0) 1235 239 670, 24/7  
Languages spoken All official European languages.

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### 2.1.1 Regulation (EC) No. 1272/2008 (CLP)

Asp. Tox. 1; H304  
Acute Tox. 4; H332  
Carc. 1B; H350  
Repr. 2; H361d  
STOT RE 2; H373 (Thymus, Liver, blood effects)  
Aquatic Acute 1; H400  
Aquatic Chronic 1; H410

### 2.2 Label elements

Product Name V3015a-LIGHT CYCLE OIL-Gas oils (petroleum), heavy vacuum

Hazard Pictogram(s)



Signal Word(s) Danger

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Hazard Statement(s) H304: May be fatal if swallowed and enters airways.  
H332: Harmful if inhaled.  
H350: May cause cancer.  
H361d: Suspected of damaging the unborn child.  
H373: May cause damage to organs through prolonged or repeated exposure:  
Thymus, Liver, blood effects  
H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statement(s) P201: Obtain special instructions before use.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P281: Use personal protective equipment as required.  
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or  
doctor/physician.  
P331: Do NOT induce vomiting.  
P273: Avoid release to the environment.

Supplemental information EUH066: Repeated exposure may cause skin dryness or cracking.

## 2.3 Other hazards

May form explosive mixture with air. The vapour is heavier than air; beware of pits and confined spaces. May cause irritation to eyes and air passages.  
Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

SUBSTANCE	CAS No.	EC No.	REACH Registration No.	%W/W
Gas oils (petroleum), heavy vacuum	64741-57-7	265-058-3	-	100

## SECTION 4: FIRST AID MEASURES



### 4.1 Description of first aid measures

Self-protection of the first aider

The vapour is heavier than air; beware of pits and confined spaces. If it is suspected that fumes are still present, the responder should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Avoid all contact. Do not ingest. If swallowed then seek immediate medical assistance.

H2S Warning:

Hydrogen sulphide (H<sub>2</sub>S) can accumulate in the headspace of storage tanks and reach potentially hazardous concentrations.

If there is any suspicion of inhalation: A self contained breathing apparatus should be worn. Remove to fresh air immediately.

Inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If symptoms persist, obtain medical attention.

Skin Contact

IF ON SKIN (or hair): Remove contaminated clothing immediately and drench affected skin with plenty of water, then wash with soap and water. If irritation (redness, rash, blistering) develops, get medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Do not induce vomiting because of risk of aspiration into the

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

<b>4.2</b>	<b>Most important symptoms and effects, both acute and delayed</b>	lungs. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. If unconscious, place in recovery position and get medical attention immediately. Do not give anything by mouth to an unconscious person. Get medical attention immediately. Do not wait for symptoms to appear. Inhalation: Vapour may be irritant to the respiratory tract. Skin Contact: Repeated and/or prolonged skin contact may cause irritation. Eye Contact: May cause eye irritation. Ingestion: Aspiration hazard. Aspiration into the lungs may cause chemical pneumonitis, which can be fatal.
<b>4.3</b>	<b>Indication of any immediate medical attention and special treatment needed</b>	If breathing is laboured, oxygen should be administered by qualified personnel. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). IF INHALED: If unconscious, place in recovery position and get medical attention immediately. Administer oxygen if available and artificial respiration if necessary. IF SWALLOWED: Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs.
	Notes to a physician:	

## SECTION 5: FIREFIGHTING MEASURES

<b>5.1</b>	<b>Extinguishing media</b> Suitable Extinguishing media Unsuitable extinguishing media	Foam, Carbon dioxide, Water fog or dry powder. Do not use water jet. Direct water jet may spread the fire.
<b>5.2</b>	<b>Special hazards arising from the substance or mixture</b>	Not flammable but will support combustion. The vapour is heavier than air; beware of pits and confined spaces. Will float and can be reignited on surface water. Decomposes in a fire giving off toxic fumes: A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. If sulphur compounds are present in appreciable amounts, combustion products may include also H <sub>2</sub> S and SO <sub>x</sub> (sulfur oxides) or sulfuric acid
<b>5.3</b>	<b>Advice for fire-fighters</b>	Fight fire with normal precautions from a reasonable distance. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire. Avoid release to the environment. Dike fire control water for later disposal.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>6.1</b>	<b>Personal precautions, protective equipment and emergency procedures</b>	Caution - spillages may be slippery. Ensure operatives are trained to minimise exposures. Ensure suitable personal protection during removal of spillages. Eliminate sources of ignition. Shut off leaks if without risk. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid all contact with substance. Ensure adequate ventilation. Do not breathe vapour. Do not ingest. If swallowed then seek immediate medical assistance. Do not use sparking tools.
	H <sub>2</sub> S Warning:	Product may release Hydrogen Sulphide. Exposure controls - These controls may include: Segregation of areas, Access only to authorised persons, Permit to work systems, Confined space working procedures, Area H <sub>2</sub> S alarms, Personal H <sub>2</sub> S alarms, Personal escape sets, H <sub>2</sub> S awareness training. Please see section 8 for appropriate personal protection equipment
	Small spillages:	Wear flame-resistant antistatic protective clothing.
	Large spillages:	Evacuate the area and keep personnel upwind. Drench contaminated clothing with water before removing to avoid risk of sparks from static electricity. Avoid all contact. Wear chemical protection suit and breathing apparatus. See Also Section: 8.
<b>6.2</b>	<b>Environmental precautions</b>	Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body. If necessary: Dike area to contain the spill and prevent releases to sewers, drains, or other waterways.
<b>6.3</b>	<b>Methods and material for containment and cleaning</b>	Provided it is safe to do so, isolate the source of the leak. The vapour is heavier

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

up	than air; beware of pits and confined spaces. Ensure that the equipment is adequately grounded. Allow small spillages to evaporate provided there is adequate ventilation.
Spillages onto land:	In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Dispose of this material and its container as hazardous waste. <b>Small spillages:</b> Allow small spillages to evaporate provided there is adequate ventilation. Wear flame-resistant antistatic protective clothing. <b>Large spillages:</b> Cover spillage with foam to reduce evaporation. Do not use water jet.
Spillages on water or at sea:	Collect as much as possible in clean container for reuse or disposal. <b>Small spillages:</b> Contain product with floating barriers or other equipment. Collect spilled product by absorbing with specific floating absorbents. <b>Large spillages:</b> Open waters should be contained with floating barriers or other mechanical means and recovered, only if this is strictly necessary and if fire/explosion risks can be adequately prevented. Otherwise control the spreading of the spillage, and let the substance evaporate naturally.
6.4 Reference to other sections	See Section: 8,13

## SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling	Obtain special instructions before use. Keep away from sources of ignition - No smoking. Use only outdoors or in a well-ventilated area. Prevent vapour build up by providing adequate ventilation during and after use. Take action to prevent static discharges. Use non-sparking tools. All parts of the plant and equipment should be electrically bonded together and connected to earth. Electrical continuity should be checked at regular intervals. Antistatic clothing and footwear should be used. The vapour is heavier than air; beware of pits and confined spaces. Avoid all contact with substance. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe vapour. See Section: 8. Keep good industrial hygiene. Wash hands thoroughly after handling. Contaminated clothing should be thoroughly cleaned.
H2S Warning:	Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. These controls may include: Segregation of areas, Access only to authorised persons, Permit to work systems, Confined space working procedures, Area H2S alarms, Personal H2S alarms, Personal escape sets, H2S awareness training.
7.2 Conditions for safe storage, including any incompatibilities	Light hydrocarbon vapours can build up in the headspace of containers. These can cause flammability / explosion hazards. Bund storage facilities to prevent soil and water pollution in the event of spillage. Keep only in original packaging. Keep containers properly sealed when not in use. Protect from sunlight. Containers of this material may be hazardous when empty since they retain product residue. Empty container may contain product residue which may result in flammable or explosive vapours inside the container.
Storage temperature	Stable at ambient temperatures.
Storage measures	Keep only in original container.
Incompatible materials	Keep away from oxidising agents.
7.3 Specific end use(s)	See Section: 1.2 and/or Exposure Scenario.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters	
8.1.1 Occupational Exposure Limits	No Occupational Exposure Limit assigned. Users are advised to consider national Occupational Exposure Limits or other equivalent values.
8.1.2 Biological limit value	Not established.

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## 8.1.3 PNECs and DNELs

DNEL: Not established.

PNEC: Gas oils (petroleum), heavy vacuum is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore individual environmental compartments PNECs are not available for this product.

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Guarantee that the eye flushing systems and safety showers are located close to the working place.

### 8.2.2 Individual protection measures, such as personal protective equipment (PPE)

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Fuels are typically used, transferred and transported in closed systems. If exposure is likely (i.e. during sampling) the following advice may be appropriate. Keep good industrial hygiene. Always wash hands before smoking, eating and drinking. Do not eat, drink or smoke at the work place.

Refer to annexes for exposure scenarios detailing use specific exposure controls

Eye/ face protection



Use eye protection according to EN 166, designed to protect against liquid splashes.

Skin protection



**Hand protection:** Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Recommended: Nitrile rubber.

**Body protection:** Wear anti-static clothing and shoes.

small scale: Wear suitable coveralls to prevent exposure to the skin.

large scale: Chemical protection suit.

Respiratory protection



When the product is heated /In case of inadequate ventilation wear respiratory protection. The use of a high efficiency filter (EN143) is recommended. Filter type A2

Closed system(s): Not normally required.

Thermal hazards

Not applicable.

## 8.2.3 Environmental Exposure Controls

Avoid release to the environment.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Liquid (May be coloured)
Odour	Characteristic
Odour threshold	Not established.
pH	Not established.
Melting point/freezing point	< 30 °C @ 101 kPa
Initial boiling point and boiling range	350 – 600 °C
Flash point	> 75 °C

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Evaporation rate	Not established.
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Not established.
Vapour pressure	> 0.5 kPa @ 20°C
Vapour density	> 1
Relative density	0.80 – 0.99 g/cm <sup>3</sup> @ 15 °C
Solubility(ies)	Slightly soluble: 0.4 mg/l @ 20 °C
Partition coefficient: n-octanol/water	2.7-6
Auto-ignition temperature	> 337 °C
Decomposition Temperature	Not established.
Viscosity	7 – 20.5 mm <sup>2</sup> /s @ 40 °C (<60 mm <sup>2</sup> /s @ 100 °C)
Explosive properties	Not explosive. (Vapour may create explosive atmosphere.)
Oxidising properties	Not oxidising.
<b>9.2 Other information</b>	None known.

## SECTION 10: STABILITY AND REACTIVITY

<b>10.1 Stability and reactivity</b>	Stable under normal conditions. Reacts with - Strong oxidising agents
<b>10.2 Chemical stability</b>	Stable under normal conditions. Hazardous polymerisation will not occur. Product may release Hydrogen Sulphide.
<b>10.3 Possibility of hazardous reactions</b>	Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Product may release Hydrogen Sulphide.
<b>10.4 Conditions to avoid</b>	Elevated temperature: > 50 °C Keep away from heat, sources of ignition and direct sunlight.
<b>10.5 Incompatible materials</b>	Keep away from oxidising agents. Strong Acids and Alkalis.
<b>10.6 Hazardous decomposition product(s)</b>	A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. Decomposes in a fire giving off toxic fumes: CO <sub>x</sub> , H <sub>2</sub> S, SO <sub>x</sub> ,

## SECTION 11: TOXICOLOGICAL INFORMATION

<b>11.1 Information on toxicological effects</b>	All test data taken from existing ECHA registrations for the substances mentioned.
<b>Acute toxicity - Ingestion</b>	Based upon the available data, the classification criteria are not met. LD50 (oral,rat) mg/kg: >2000 (OECD 401)
<b>Acute toxicity - Inhalation</b>	Acute Tox. 4; Harmful if inhaled. LC50 (inhalation,rat) mg/l/4h: 4.1 (EPA OTS 798.1150)
<b>Acute toxicity - Skin Contact</b>	Based upon the available data, the classification criteria are not met. LD50 (skin,rabbit) mg/kg: >2000 (OECD 434)
<b>Skin corrosion/irritation</b>	Based upon the available data, the classification criteria are not met. Not irritating to skin. (rabbit) (OECD 404) EUH066: Repeated exposure may cause skin dryness or cracking. (rat) (OECD 410)
<b>Serious eye damage/irritation</b>	Based upon the available data, the classification criteria are not met. Not irritating to eyes. (rabbit) (EU Method B.5)
<b>Respiratory or skin sensitization</b>	Based upon the available data, the classification criteria are not met. Sensitisation (guinea pig) - Negative (OECD 406)
<b>Germ cell mutagenicity</b>	Based upon the available data, the classification criteria are not met. ECHA Registration Endpoint summary: Not classified. Studies showed no consistent evidence of mutagenic activity.
<b>Carcinogenicity</b>	Carc. 1B; May cause cancer. ECHA Registration Endpoint summary: Positive (mouse)
<b>Reproductive toxicity</b>	Repr. 2; H361d: Suspected of damaging the unborn child. ECHA Registration Endpoint summary: Reproductive toxicity: Negative Developmental toxicity: Positive
<b>STOT - single exposure</b>	Based upon the available data, the classification criteria are not met. Weight of evidence approach
<b>STOT - repeated exposure</b>	STOT RE 2; May cause damage to organs through prolonged or repeated

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

	exposure.
	Oral: No data
	Inhalation: No data
<b>Aspiration hazard</b>	Dermal: NOAEL 1.06 mg/kg bw/day (rat) (OECD 410) Asp. Tox. 1; May be fatal if swallowed and enters airways. Viscosity: 7 – 20.5 mm <sup>2</sup> /s @ 40 °C (<60 mm <sup>2</sup> /s @ 100 °C)
<b>11.2 Other information</b>	None.

## SECTION 12: ECOLOGICAL INFORMATION

<b>12.1 Toxicity</b>	Aquatic Acute 1; Very toxic to aquatic life. Aquatic Chronic 1; Very toxic to aquatic life with long lasting effects. Short Term (acute): EL50 48hr (Daphnia magna) 0.22 mg/l (OECD 202) Long Term (Chronic): The aquatic toxicity was estimated using the PETROTOX computer model. Estimated: 0.1 mg/l (Fish)
<b>12.2 Persistence and degradability</b>	Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
<b>12.3 Bioaccumulative potential</b>	Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
<b>12.4 Mobility in soil</b>	Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.
<b>12.5 Results of PBT and vPvB assessment</b>	Not classified as PBT or vPvB.
<b>12.6 Other adverse effects</b>	None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

<b>13.1 Waste treatment methods</b>	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Disposal should be in accordance with local, state or national legislation. Containers of this material may be hazardous when empty since they retain product residue. Containers must not be punctured or destroyed by burning, even when empty. Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company. Waste code: Fuel Oil (13 07 01)
-------------------------------------	---

## SECTION 14: TRANSPORT INFORMATION

	<b>ADR/RID</b>	<b>IMDG/ADN</b>
<b>14.1 UN number</b>	UN 1202	UN 1202
<b>14.2 Proper Shipping Name</b>	GAS OIL	GAS OIL
<b>14.3 Transport hazard class(es)</b>	3	3+(N1, CMR, F)
<b>14.4 Packing group</b>	III	III
<b>14.5 Environmental hazards</b>	MILIEUGEVAARLIJK / ENVIRONMENTALLY HAZARDOUS/ UMWELTGEFÄHREND /DANGEREUX POUR/ L'ENVIRONNEMENT	
<b>14.6 Special precautions for user</b>	See Section: 2	
<b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	This product is being carried under the scope of MARPOL Annex 1. Special Precautions: Refer to Chapter 7 'Handling and Storage' for special precautions which a user needs to be aware of, or needs to comply with, in connection with transport.	
<b>14.8 Additional Information</b>	HIN: 30 Tunnel Code: 3 (D/E) Limited Quantity: 5L	EmS: F-E, S-E Limited Quantity: 5L

## SECTION 15: REGULATORY INFORMATION

<b>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	
<b>15.1.1 EU regulations</b>	Authorisations and/or Restrictions On Use
Annex XVII (Restrictions)	In accordance with REACH Annex XVII entry 30 (c) this substance is exempt

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Seveso	from Entry 28 and 29 of REACH Annex XVII as it is to be sold as a fuel in a closed system.
<b>15.1.2 National regulations</b>	Upper Tier: 25000 tonnes Lower Tier: 2500 tonnes None
<b>15.2 Chemical Safety Assessment</b>	A REACH chemical safety assessment (CSA) has been carried out. Refer to annexes for exposure scenarios detailing use specific exposure controls.

## SECTION 16: OTHER INFORMATION

### Sections indicated with the following have been revised

Header and Section 1.3

Updated version and date. Please review SDS with care.

### References:

Existing ECHA registration(s) for Gas oils (petroleum), heavy vacuum (CAS No. 64741-57-7) and Chemical Safety Report.

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830.

### LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
OECD	Organisation for Economic Cooperation and Development

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vitol SA gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vitol SA accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

### Annex to the extended Safety Data Sheet (eSDS)

See below -



# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Gas oils (petroleum), heavy vacuum

CAS No. 64741-57-7  
EINECS No. 265-058-3

### Summary of Parameters

Physical parameters			
Vapour pressure (kPa)		0.02 - 0.791 kPa @ 120°C	
Partition Coefficient (log K <sub>ow</sub> )		Individual components vary between 2.92 and 20.43	
Aqueous solubility (mg/l)		Individual components vary between 2.7E-12 and 2.0E+02 Value used for environmental exposure assessment= 0.13	
Molecular weight		Not applicable	
Biodegradability		Not defined	
Human Health (DNEL)			
Workers	Short term	Inhalation (mg/m <sup>3</sup> )	4700
		Dermal (mg/kg bw/day)	Not defined
	Long Term	Inhalation (mg/m <sup>3</sup> )	0.18
		Dermal (mg/kg bw/day)	0.065
Consumer	Inhalation (mg/m <sup>3</sup> )		Not defined
	Dermal (mg/kg bw/day)		Not defined
	Oral (mg/kg bw/day)		0.015
Environmental Parameters (PNECs)			
Gas oils (petroleum), heavy vacuum is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore individual environmental compartments PNECs are not available for this product.			

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Contents

Number	Title	Page:
Exposure scenario 1	Distribution of Gas oils (petroleum), heavy vacuum	11
Exposure scenario 2	Formulation and (re)packing of Gas oils (petroleum), heavy vacuum	15
Exposure scenario 3	Use as a fuel (Industrial)	19
Exposure scenario 4	Use as a fuel (Professional)	22

## Contributing Scenarios

### PROC Codes

- PROC1 Use in closed process, no likelihood of exposure
- PROC2 Use in closed, continuous process with occasional controlled exposure  
(Storage) Use in closed, continuous process with occasional controlled exposure, bulk Storage  
(fuel filtering) In-line filter or centrifuge.
- PROC3 Use in closed batch process (synthesis or formulation)
- PROC8a (manual) Manual transfer/pouring from containers  
(maintenance) Clean down and maintenance of vessels and containers.
- PROC8b (bulk) Bulk transfers (closed systems).  
(marine) Marine vessel or barge loading.  
(road and rail) Road tanker or railcar loading.  
(Drum) Drum/batch transfers.  
(refuelling) Refueling residences, heavy equipment.
- PROC15 Use as laboratory reagent
- PROC16 Using material as fuel sources, limited exposure to unburned product to be expected

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Exposure Scenario 1 –Distribution of Gas oils (petroleum), heavy vacuum

1.0 Contributing Scenarios	
Sector of uses SU	SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
Process category [PROC]	PROC1 PROC2 PROC2 (Storage) PROC2 (Sampling) PROC3 PROC8a (Maintenance) PROC8b (Marine) PROC8b (Road/Rail) PROC15
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC4 Industrial use of processing aids in processes and products, not becoming part of articles ERC5 Industrial use resulting in inclusion into or onto a matrix ERC6a Industrial use resulting in manufacture of another substance (use of intermediates) ERC6b Industrial use of reactive processing aids ERC6c Industrial use of monomers for manufacture of thermo-plastics ERC6d Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers ERC7 Industrial use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 1.1b.v1

2.0 Operational conditions and risk management measures		
<b>2.1 Control of worker exposure</b>		
<b>Product characteristics</b>		
Physical form of product	Liquid with low volatility.	
Vapour pressure (kPa)	<0.5 @ STP	
Concentration of substance in product	Covers concentrations up to 100%	
<b>Human factors not influenced by risk management</b>		
Potential exposure area	Not defined	
<b>Frequency and duration of use</b>		
Exposure duration per day	PROC1, PROC8a (Maintenance), PROC15	Covers daily exposures up to 8 hours (unless stated differently).
	PROC2 (Storage), PROC3, PROC8b (Marine), PROC8b (Road/Rail)	Covers exposure up to 4 hours
	PROC2, PROC2 (Sampling)	Covers exposure up to 15 minutes
Exposure duration per year	300 days per year	
<b>Other operational conditions affecting worker exposure</b>		
Area of use	All contributing scenarios	Not defined (default = Indoor)
Characteristics of the surroundings	Not defined	
<b>General measures applicable to all activities</b>		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.		
<b>General measures (carcinogens)</b>		
Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised		

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

### Technical conditions of use

PROC1, PROC2, PROC3	Handle substance within a closed system.
PROC2 (Sampling)	Sample via a closed loop or other system to avoid exposure.
PROC15	Use fume cupboard. (Efficiency of at least 90%)

### Organisational measures

PROC8b (Marine)	Transfer via enclosed lines. Clear transfer lines prior to de-coupling. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
PROC8a (Maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. (Dermal: Efficiency of at least 75%)
PROC8b (Road/Rail)	IF exposed: > 1 hour: Ensure material transfers are under containment or extract ventilation.
All other PROC's	No specific measures identified.

### Risk management measures related to human health

Respiratory protection	No special measures are required.	
Hand and/or Skin protection	PROC15	Wear suitable gloves tested to EN374. Efficiency of at least 80%
	PROC8a (Maintenance)	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
	All other PROC's	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Efficiency of at least: 90%.
Eye Protection	No special measures are required.	

### Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply

Assumes activities are at ambient temperature (unless stated differently).  
Assumes a good basic standard of occupational hygiene is implemented.  
Use long handled tools where possible. - PROC8a (Maintenance)  
Decontaminate tools, equipment and personal protective equipment in a segregated area. - PROC8a (Maintenance)

### 2.2 Control of environmental exposure

#### Amounts used

Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tons/year):	1.7E+06
Fraction of Regional tonnage used locally: tons/year	2.0E-03
Annual site tonnage (tons/year):	3.4E+03
Average daily use (kg/day)	3.4E+04

#### Environment factors not influenced by risk management

Flow rate of receiving surface water (m <sup>3</sup> /d):	18,000
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

#### Operational conditions

Emission days (days/year):	100
Release fraction to air from process (initial release prior to RMM):	1.0E-04
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-07
Release fraction to soil from process (initial release prior to RMM):	1.0E-05

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Treat air emission to provide a typical removal efficiency of (%):	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	0
Treat soil emission to provide a typical removal efficiency of (%):	0

#### Organisational measures to prevent/limit release from site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m <sup>3</sup> /d)	2000
Degradation effectiveness (%)	90.4

#### Conditions and measures related to external treatment of waste for disposal

External treatment and disposal of waste should comply with applicable local and/or national regulations.

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Substance release quantities after risk management measures

Release to waste water from process (mg/l)	Not defined
Maximum allowable site tonnage (MSafe) (kg/d):	4.6E+04

## 3. Exposure estimation and reference to its source

### 3.1 Human exposure prediction

Exposure assessment (method/calculation model) ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m <sup>3</sup> )	Risk characterisation ratio (RCR)	dermal exposure (mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	0.01	0.04	0.03	0.57	0.61
PROC2	0.04	0.19	0.03	0.5	0.76
PROC2 (Storage)	0.04	0.21	0.03	0.57	0.78
PROC2 (Sampling)	0.04	0.19	0.03	0.57	0.76
PROC3	0.04	0.21	0.03	0.57	0.78
PROC8a (Maintenance)	0.00	0.01	0.05	0.83	0.85
PROC8b (Marine)	0.06	0.36	0.03	0.57	0.92
PROC8b (Road/Rail)	0.03	0.19	0.03	0.57	0.76
PROC15	0.05	0.28	0.01	0.10	0.38

### 3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Gas oils (petroleum), heavy vacuum is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore individual environmental compartments PNECs are not available for this product.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	1.7E-04 mg/l	1.6E-05 mg/l	1.6E-06 mg/l	5.2E-02 mg/kg ww	1.4 mg/kg ww	3.1E-02 mg/kg ww
Risk characterisation ratio (RCR)	8.8E-04	2.8E-03	2.8E-04	2.1E-05	5.7E-03	3.5E-04

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	11	0.73
Inhalation	0.016	3.2E-04

## 4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

	equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.	
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Exposure Scenario 2 – Formulation and (re)packing of Gas oils (petroleum), heavy vacuum

1.0 Contributing Scenarios	
Sector of uses SU	SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
Process category [PROC]	PROC1 PROC2 PROC2 (Storage) PROC2 (Sampling) PROC3 PROC8a (Maintenance) PROC8b (Marine) PROC8b (Road/Rail) PROC8b (Drum) PROC15
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC2 Formulation of preparations
Specific Environmental Release Categories SPERC	ESVOC SpERC 2.2.v1

2.0 Operational conditions and risk management measures		
<b>2.1 Control of worker exposure</b>		
<b>Product characteristics</b>		
Physical form of product	Liquid with low volatility.	
Vapour pressure (kPa)	<0.5 @ STP	
Concentration of substance in product	Covers concentrations up to 100%	
<b>Human factors not influenced by risk management</b>		
Potential exposure area	Not defined	
<b>Frequency and duration of use</b>		
Exposure duration per day	PROC1, PROC8a (Maintenance), PROC15	Covers daily exposures up to 8 hours (unless stated differently).
	PROC2 (Storage), PROC3, PROC8b (Marine)	Covers exposure up to 1-4 hours
	PROC8b (Road/Rail), PROC8b (Drum)	Covers exposure up to 1 hour(s)
	PROC2, PROC2 (Sampling)	Covers exposure up to 15 minutes
Exposure duration per year	300 days per year	
<b>Other operational conditions affecting worker exposure</b>		
Area of use	All contributing scenarios	Not defined (default = Indoor)
Characteristics of the surroundings	Not defined	
<b>General measures applicable to all activities</b>		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.		
<b>General measures (carcinogens)</b>		
Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.		
<b>Technical conditions of use</b>		

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

PROC1, PROC2, PROC2 (Sampling), PROC3	Handle substance within a closed system.	
PROC2, PROC2 (Sampling), PROC3	Sample via a closed loop or other system to avoid exposure.	
PROC8b (Marine)	Transfer via enclosed lines	
PROC8b (Road/Rail), PROC8b (Drum)	Ensure material transfers are under containment or extract ventilation.	
PROC8b (Drum)	In case of Indoor use: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Efficiency of at least 97%	
PROC15	Use fume cupboard. Efficiency of at least 90%	
<b>Organisational measures</b>		
PROC8a (Maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Use long handled tools where possible.	
PROC8b (Marine)	Clear transfer lines prior to de-coupling. Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.	
PROC8b (Road/Rail)	IF exposed: > 1 hour: Ensure material transfers are under containment or extract ventilation.	
All other PROC's	No specific measures identified.	
<b>Risk management measures related to human health</b>		
Respiratory protection	No special measures are required.	
Hand and/or Skin protection	All other PROC's	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Efficiency of at least 90%
	PROC8a (Maintenance)	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Efficiency of at least 80%
	PROC15	Wear suitable gloves tested to EN374. Efficiency of at least 80%
Eye Protection	No special measures are required.	
<b>Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply</b>		
Assumes activities are at ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented. Use long handled tools where possible. - PROC8a (Maintenance) Decontaminate tools, equipment and personal protective equipment in a segregated area. - PROC8a (Maintenance)		
<b>2.2 Control of environmental exposure</b>		
<b>Amounts used</b>		
Fraction of EU tonnage used in region:	0.1	
Regional use tonnage (tons/year):	1.7E+05	
Fraction of Regional tonnage used locally: tons/year	1.8E-01	
Annual site tonnage (tons/year):	3.0E+04	
Average daily use (kg/day)	1.0E+05	
<b>Environment factors not influenced by risk management</b>		
Flow rate of receiving surface water (m <sup>3</sup> /d):	18,000	
Local freshwater dilution factor:	10	
Local marine water dilution factor:	100	
<b>Operational conditions</b>		
Emission days (days/year):	300	
Release fraction to air from process (initial release prior to RMM):	2.2E-03	
Release fraction to wastewater from process (initial release prior to RMM):	5.0E-06	
Release fraction to soil from process (initial release prior to RMM):	1.0E-04	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>		
Treat air emission to provide a typical removal efficiency of (%):	0	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	80.1	
Treat soil emission to provide a typical removal efficiency of (%):	0	
Common practices vary across sites thus conservative process release estimates used.		
<b>Organisational measures to prevent/limit release from site</b>		
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.		
<b>Conditions and measures related to municipal sewage treatment plant</b>		
Size of municipal sewage system/treatment plant (m <sup>3</sup> /d)	2000	
Degradation effectiveness (%)	90.4	
<b>Conditions and measures related to external treatment of waste for disposal</b>		



# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

External treatment and disposal of waste should comply with applicable local and/or national regulations.

### Substance release quantities after risk management measures

Release to waste water from process (mg/l)	Not defined
Maximum allowable site tonnage (MSafe) (kg/d):	1.1E+05

## 3. Exposure estimation and reference to its source

### 3.1 Human exposure prediction

Exposure assessment (method/calculation model) | ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m <sup>3</sup> )	Risk characterisation ratio (RCR)	dermal exposure (mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	0.01	0.04	0.03	0.57	0.61
PROC2	0.04	0.19	0.03	0.57	0.76
PROC2 (Storage)	0.04	0.21	0.03	0.57	0.78
PROC2 (Sampling)	0.04	0.19	0.03	0.57	0.76
PROC3	0.04	0.21	0.03	0.57	0.78
PROC8a (Maintenance)	0.00	0.013	0.05	0.83	0.85
PROC8b (Marine)	0.06	0.36	0.03	0.57	0.92
PROC8b (Road/Rail)	0.03	0.19	0.03	0.57	0.76
PROC8b (Drum)	0.02	0.12	0.03	0.57	0.68
PROC15	0.05	0.28	0.01	0.10	0.38

### 3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) | The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Gas oils (petroleum), heavy vacuum is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore individual environmental compartments PNECs are not available for this product.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	2.5E-02 mg/l	2.4E-03 mg/l	2.4E-04 mg/l	6.3E-02 mg/kg ww	1.8 mg/kg ww	4.2E-02 mg/kg ww
Risk characterisation ratio (RCR)	1.3E-01	4.1E-01	4.1E-02	3.1E-03	4.8E-01	4.8E-02

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	1.1E+02	7.7*
Inhalation	1.6E+01	3.2E-01

\*The Lead Registrant has subsequently performed a new environmental risk assessment and all RCRs < 1. To be communicated in the next ES update

## 4. Evaluation guidance to downstream user

For scaling see | Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

	are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).	
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.	
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Exposure Scenario 3 – Use as a fuel (Industrial)

1.0 Contributing Scenarios	
Sector of uses SU	SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
Process category [PROC]	PROC1 PROC2 PROC2 (Fuel filtering) PROC2 (Storage) PROC3 PROC8a (Maintenance) PROC8b (Bulk) PROC8b (Drum) PROC16
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC7 Industrial use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 7.12a.v1

2.0 Operational conditions and risk management measures		
<b>2.1 Control of worker exposure</b>		
<b>Product characteristics</b>		
Physical form of product	Liquid with low volatility.	
Vapour pressure (kPa)	<0.5 @ STP	
Concentration of substance in product	Covers concentrations up to 100%	
<b>Human factors not influenced by risk management</b>		
Potential exposure area	Not defined	
<b>Frequency and duration of use</b>		
Exposure duration per day	PROC1, PROC8a (Maintenance), PROC16	Covers daily exposures up to 8 hours (unless stated differently).
	PROC2 (Fuel filtering), PROC2 (Storage), PROC8b (Bulk)	Covers exposure up to 4 hour(s)
	PROC3	Covers exposure up to 1 - 4 hour(s)
	PROC2, PROC8b (Drum)	Covers exposure up to 1 hour(s)
Exposure duration per year	300 days per year	
<b>Other operational conditions affecting worker exposure</b>		
Area of use	PROC1,	Outdoor
	All other PROC's	Not defined, Default - Indoor
Characteristics of the surroundings	Not defined	
<b>General measures applicable to all activities</b>		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.		
<b>General measures (carcinogens)</b>		
Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.		
<b>Technical conditions of use</b>		

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

PROC1, PROC2, PROC2 (Storage), PROC3, PROC16	Handle substance within a closed system.	
PROC2 (Fuel filtering), PROC2 (Storage), PROC8b (Drum), PROC16	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
PROC8b (Bulk)	Transfer via enclosed lines	
<b>Organisational measures</b>		
PROC8a (maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Dermal Efficiency of at least 75%	
All other PROC's	No specific measures identified.	
<b>Risk management measures related to human health</b>		
Respiratory protection	No special measures are required.	
Hand and/or Skin protection	PROC1, PROC2, PROC2 (Fuel filtering), PROC2 (Storage), PROC3, PROC8b (Bulk), PROC8b (Drum), PROC16	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Efficiency of at least 90%
	PROC8a (Maintenance)	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Efficiency of at least 95%
Eye Protection	No special measures are required.	
<b>Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply</b>		
Use long handled tools where possible. - PROC8a (maintenance)		
Decontaminate tools, equipment and personal protective equipment in a segregated area. - PROC8a (maintenance)		
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). – PROC16		
<b>2.2 Control of environmental exposure</b>		
<b>Amounts used</b>		
Fraction of EU tonnage used in region:	0.1	
Regional use tonnage (tons/year):	1.3E+05	
Fraction of Regional tonnage used locally: tons/year	1.0E+00	
Annual site tonnage (tons/year):	1.3E+05	
Average daily use (kg/day)	4.4E+05	
<b>Environment factors not influenced by risk management</b>		
Flow rate of receiving surface water (m <sup>3</sup> /d):	18,000	
Local freshwater dilution factor:	10	
Local marine water dilution factor:	100	
<b>Operational conditions</b>		
Emission days (days/year):	300	
Release fraction to air from process (initial release prior to RMM):	5.0E-03	
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05	
Release fraction to soil from process (initial release prior to RMM):	0	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>		
Treat air emission to provide a typical removal efficiency of (%):	95.0	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	97.7	
Treat soil emission to provide a typical removal efficiency of (%):	76.3	
Common practices vary across sites thus conservative process release estimates used. Prevent discharge of undissolved substance to or recover from onsite wastewater.		
<b>Organisational measures to prevent/limit release from site</b>		
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.		
<b>Conditions and measures related to municipal sewage treatment plant</b>		
Size of municipal sewage system/treatment plant (m <sup>3</sup> /d)	2000	
Degradation effectiveness (%)	97.7	
<b>Conditions and measures related to external treatment of waste for disposal</b>		
This substance is consumed during use and no waste of the substance is generated.		
Combustion emissions limited by required exhaust emission controls.		
Combustion emissions considered in regional exposure assessment.		
<b>Substance release quantities after risk management measures</b>		
Release to waste water from process (mg/l)	Not defined	

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Maximum allowable site tonnage (MSafe) (kg/d):	4.4E+05
--	---------

### 3. Exposure estimation and reference to its source

#### 3.1 Human exposure prediction

Exposure assessment (method/calculation model) | ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m <sup>3</sup> )	Risk characterisation ratio (RCR)	dermal exposure(mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	0.01	0.039	0.03	0.57	0.61
PROC2	0.03	0.17	0.03	0.57	0.73
PROC2 (Fuel filtering)	0.04	0.21	0.03	0.57	0.78
PROC2 (Storage)	0.04	0.21	0.03	0.57	0.78
PROC3	0.04	0.21	0.03	0.57	0.92
PROC8a (Maintenance)	0.00	0.013	0.05	0.83	0.85
PROC8b (Bulk)	0.06	0.36	0.03	0.57	0.92
PROC8b (Drum)	0.03	0.19	0.03	0.57	0.78
PROC16	0.01	0.06	0.03	0.83	0.85

#### 3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) | The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Gas oils (petroleum), heavy vacuum is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore individual environmental compartments PNECs are not available for this product.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	4.7E-02 mg/l	4.6E-03 mg/l	4.6E-04 mg/l	5.7E-02 mg/kg ww	2.2 mg/kg ww	7.9E-02 mg/kg ww
Risk characterisation ratio (RCR)	2.5E-01	7.8E-01	7.8E-02	1.4E-03	9.1E-01	9.1E-02

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	52	3.4*
Inhalation	7.2	1.4E01

\*The Lead Registrant has subsequently performed a new environmental risk assessment and all RCRs < 1. To be communicated in the next ES update

### 4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

 **Vitol**  
Gas oils (petroleum), heavy  
vacuum V3015a

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

	Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.	
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## Exposure Scenario 4 – Use as a fuel (Professional)

1.0 Contributing Scenarios	
Sector of uses SU	SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process category [PROC]	PROC1 PROC2 PROC2 (Storage) PROC3 PROC8a (Maintenance) PROC8b (Bulk) PROC8b (Drum) PROC 8b (Refueling) PROC16
Chemical product category [PC]	not applicable
Article Categories [AC]	not applicable
Environmental release categories [ERC]	ERC9a Wide dispersive indoor use of substances in closed systems ERC9b Wide dispersive outdoor use of substances in closed systems
Specific Environmental Release Categories SPERC	ESVOC SpERC 9.12b.v1

2.0 Operational conditions and risk management measures		
<b>2.1 Control of worker exposure</b>		
<b>Product characteristics</b>		
Physical form of product	Liquid with low volatility.	
Vapour pressure (kPa)	<0.5 @ STP	
Concentration of substance in product	Covers concentrations up to 100%	
<b>Human factors not influenced by risk management</b>		
Potential exposure area	Not defined	
<b>Frequency and duration of use</b>		
Exposure duration per day	PROC1, PROC8a (Maintenance), PROC16	Covers daily exposures up to 8 hours (unless stated differently).
	PROC2 (Storage)	Covers exposure up to 4 hours
	PROC2, PROC8b (Bulk), PROC8b (Drum), PROC8b (refuelling)	Covers exposure up to 1 hour(s)
	PROC3	Covers exposure up to 15 minutes
Exposure duration per year	365 days per year	
<b>Other operational conditions affecting worker exposure</b>		
Area of use	All PROC's	Not defined, Default - Indoor
Characteristics of the surroundings	Not defined	
<b>General measures applicable to all activities</b>		
Assumes a good basic standard of occupational hygiene is implemented. Assumes use at not more than 20°C above ambient temperature, unless stated differently. Control any potential exposure using measures such as contained or enclosed systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and clear transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of the nature of exposure and aware of basic actions to minimise exposures; Ensure suitable personal protective equipment is available; Clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; consider the need for health surveillance; identify and implement corrective actions.		
<b>General measures (carcinogens)</b>		
Consider technical advances and process upgrades (including automation) for the elimination of releases. minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenario; clear up spills immediately and dispose of waste safely. Ensure safe		

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

### Technical conditions of use

PROC1, PROC2, PROC2 (Storage), PROC3, PROC16	Handle substance within a closed system.
PROC2, PROC3, PROC8b (bulk), PROC8b (Drum)	Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
PROC2 (Storage), PROC8a (maintenance)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

### Organisational measures

PROC8a (maintenance)	Drain down and flush system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Dermal Efficiency of at least 75%
All other PROC's	No specific measures identified.

### Risk management measures related to human health

Respiratory protection	No special measures are required.	
Hand and/or Skin protection	PROC1, PROC2 (Storage), PROC3, PROC8b (Drum), PROC8b (refuelling),	Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Efficiency of at least 90%
	PROC2, PROC8a (maintenance)	Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Efficiency of at least 95%
Eye Protection	No special measures are required.	

### Additional good practice advice beyond the REACH CSA. Obligations according to Article 37(4) of REACH do not apply

Use long handled tools where possible. - PROC8a (maintenance)  
 Decontaminate tools, equipment and personal protective equipment in a segregated area. - PROC8a (maintenance)  
 Clear transfer lines prior to de-coupling. Retain drain downs in sealed storage pending disposal or for subsequent recycle. - PROC8b (bulk), PROC8b (Drum)

### 2.2 Control of environmental exposure

#### Amounts used

Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tons/year):	3.4E+04
Fraction of Regional tonnage used locally: tons/year	5.0E-04
Annual site tonnage (tons/year):	1.7E+01
Average daily use (kg/day)	4.7E+01

#### Environment factors not influenced by risk management

Flow rate of receiving surface water (m <sup>3</sup> /d):	18,000
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

#### Operational conditions

Emission days (days/year):	365
Release fraction to air from process (initial release prior to RMM):	1.0E-04
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-05

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Treat air emission to provide a typical removal efficiency of (%):	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of (%):	0
Treat soil emission to provide a typical removal efficiency of (%):	0

Common practices vary across sites thus conservative process release estimates used.

#### Organisational measures to prevent/limit release from site

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/treatment plant (m <sup>3</sup> /d)	2000
Degradation effectiveness (%)	90.4

#### Conditions and measures related to external treatment of waste for disposal

This substance is consumed during use and no waste of the substance is generated.  
 Combustion emissions limited by required exhaust emission controls.  
 Combustion emissions considered in regional exposure assessment.

#### Substance release quantities after risk management measures



# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Maximum allowable site tonnage (MSafe) (kg/d):	6.4E+01
--	---------

### 3. Exposure estimation and reference to its source

#### 3.1 Human exposure prediction

Exposure assessment (method/calculation model) | ECETOC TRA

Process category [PROC]	Inhalation		Dermal		Combined
	inhalation exposure (mg/m <sup>3</sup> )	Risk characterisation ratio (RCR)	dermal exposure (mg/kg bw/day)	Risk characterisation ratio (RCR)	Risk characterisation ratio (RCR)
PROC1	0.01	0.056	0.03	0.57	0.62
PROC2	0.06	0.33	0.02	0.28	0.62
PROC2 (Storage)	0.04	0.21	0.03	0.57	0.78
PROC3	0.03	0.18	0.03	0.57	0.73
PROC8a (Maintenance)	0.01	0.05	0.05	0.83	0.88
PROC8b (Bulk)	0.03	0.19	0.03	0.57	0.76
PROC8b (Drum)	0.03	0.19	0.03	0.57	0.76
PROC8b (refuelling)	0.03	0.19	0.03	0.57	0.76
PROC16	0.01	0.06	0.03	0.57	0.62

#### 3.2 Environmental exposure prediction

Exposure assessment (method/calculation model) | The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

Gas oils (petroleum), heavy vacuum is a hydrocarbon UVCB. The hydrocarbon block method is used in PETRORISK to calculate the environmental toxicity (HC5) of each group of components in the substance. These are used to estimate the environmental risk for the substance. Therefore individual environmental compartments PNECs are not available for this product.

environmental exposure	STP	freshwater	marine water	soil	freshwater sediment	marine sediment
Predicted Environmental Exposure (PEC)	2.3E-05 mg/l	1.6E-05 mg/l	2.3E-07 mg/l	5.2E-02 mg/kg ww	1.4 mg/kg ww	3.1E-02 mg/kg ww
Risk characterisation ratio (RCR)	1.2E-04	3.2E-03	3.8E-05	2.4E-04	2.9E-03	7.0E-05

Indirect exposure to humans via the environment:

Exposure route	Exposure estimation (µg/kg/day)	Risk characterisation ratio (RCR)
Oral	11	7.3E-01
Inhalation	8.7E-03	1.7E-04

### 4. Evaluation guidance to downstream user

For scaling see	Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).
Health	Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not allow the derivation of a DNEL for eye or respiratory tract irritant effects. Risk Management Measures are based on qualitative risk characterisation.

# SAFETY DATA SHEET

Revision: 5.1 Date: 10.06.2019



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Exposure assessment instrument/tool/method	Worker	ECETOC TRA
	Environment	The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.